

# Cirrus LED Flush Mount C2F Series

#### **Features**

A round floating cloud style with a white diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

#### Construction

A 22-gauge steel housing made by stamping process and painted in lighting grade white to provide long lasting finish with 3 side white screws to hold molded diffuser. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

#### **Finish**

White finish.

#### Diffuser

0.070" thick smooth white acrylic.

#### **Electrical**

Input 120VAC / 60 Hz.
Compatible with TRIAC and ELV dimmers.

#### **LED**

Integrated LED modules capable of producing: 17W = 1258 delivered lumens 27W = 1600 delivered lumens 35W = 2236 delivered lumens Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs. 90 CRI.

# Certification

All fixtures are cETLus listed for indoor damp locations. ENERGY STAR® qualified. T24-JA8 Compliant. Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

## **Options (EXCLUDES 11")**

Emergency Battery Back-Up (add -BB to the end of the model number)

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

# **Ordering Information:**

			Delivered			
	White	LED	Lumens	Adjustable CCT	DIA.	D
	C2F111600L5AJD1	17W	1258	2700K/3000K/3500K/4000K/5000K	11"	3"
	C2F142400L5AJD1	27W	1600	2700K/3000K/3500K/4000K/5000K	14"	3"
	C2F193100L5AJD1	35W	2236	2700K/3000K/3500K/4000K/5000K	19"	3"

LOCATION	DATE		
PREPARED BY	QUANTITY		
COMMENTS	FIXTURE TYPE		
CATALOG NUMBER			
















**FLUSH MOUNT** 



BATTERY BACKUP