HASSOCK & OFFICE FANS

THE 360° AIR DISTRIBUTION MAKES THIS FAN IDEAL FOR OFFICES AND COMPUTER ROOMS.



PRODUCT INFORMATION

Motor | 3-speed, 1/20 HP, 120V, 1 phase, permanently lubricated,

permanent split capacitor

Controls Front mounted rotary switch

Power Cord White, 7', 3-conductor, SPT type

Construction Impact resistant plastic grills with chemical resistant

polypropylene blade

Compliances | (4), OSHA



IDEAL FOR USE IN OFFICES, PRODUCTION LINES, KITCHENS, BEAUTY SALONS, TOLL BOOTHS, STORES AND ANYWHERE ELSE SPACE IS LIMITED.

PRODUCT INFORMATION

Motor | 2-speed, 1/300 HP, 120V, 1 phase, permanently lubricated

Controls Rear mounted rotary switch

Power Cord White, 7', 3-conductor, SPT type

Construction Zinc plated steel front grill with impact resistant plastic

rear grill and chemical resistant polypropylene blade

Compliances (L), OSHA

SPECIFICATIONS

Model	DESCRIPTION	BLADE SIZE	PRODUCT DIMENSIONS	WEIGHT (LBS.)	CUBE (FEET)	LIST PRICE
9152	12" Hassock Fan	12"	17 ⁵ / ₈ "L x 17 ¹ / ₈ "W x 14"H	13.4	2.81	\$126.00
9145	6" Clip-On Fan	6"	8½"L x 6¼"W x 10¾"H	2.1	.27	\$23.00
9146	6" Personal Fan	ο"	8 ¹ / ₈ "L x 6 ¹ / ₄ "W x 10 ³ / ₈ "H	2.1	.27	\$21.00

PERFORMANCE

1	Model	CFM			RPM		AMPS			WATTS			DB A			
		HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW
	9152	1150	1080	1010	1550	1235	965	.66	.51	.44	69	59	52	53	45	36
	9145	190	-	90	2020	-	1740	.19	-	.15	12	-	9	37	-	34
	9146	190	-	90	2020	-	1740	.19	-	.15	12	-	9	37	-	34

Performance ratings are conducted in accordance with AMCA standard 230-99. • Specifications are subject to change

