INDUSTRIAL GRADE DRUM FAI

WHEN THE GOAL IS TO MOVE A LARGE AMOUNT OF AIR, THE AIR KING DRUM FANS ARE THE PERFECT SOLUTION.

PRODUCT INFORMATION

Motor | 2-speed, 1/2 HP, 120V, 1 phase, ball bearing, permanently lubricated, permanent split capacitor (models 9942)

2-speed, 1/3 HP, 120V, 1 phase, ball bearing, permanently lubricated, permanent split capacitor (model 9936, 9236)


Controls Side mounted switch

Power Cord Black, 10', 3-conductor, SJT type

Coating Blade, Guard, and Mounts are Powder coated steel

Compliances (L), OSHA





SPECIFICATIONS

Model	DESCRIPTION	BLADE SIZE	PRODUCT DIMENSIONS	WEIGHT (LBS.)	CUBE (FEET)	LIST PRICE
9942	42" Belt Driven Drum Fan	42"	43½"L x 17½"W x 45½"H	103.2	20.04	\$685.00
9936	36" Belt Driven Drum Fan	36"	38½"L x 17½"W x 40½"H	75.4	15.79	\$620.00
9236	36" Direct Drive Drum Fan	30	38½"L x 12½"W x 40½"H	63.1	11.28	\$525.00

PERFORMANCE

		<u> </u>											
Model	CFM		RPM		AMPS		WATTS		DB A				
	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW			
9942	12900	8860	1725	1140	8.40	4.80	635	435	72	60			
9936	9140	7060	1525	1000	5.00	2.70	540	370	68	59			
9236	9630	6900	800	445	6.50	5.10	570	390	77	64			

Performance ratings are conducted in accordance with AMCA standard 230-99. • Specifications are subject to change.

