

SPECIFICATIONS
ADA SERIES
RANGE HOOD

**Included Wall Control** 



# 270 CFM/4.0 Sones (Vertical) @ 0.10" S.P. 150 CFM/1.5 Sones (Vertical) @ 0.10" S.P., 42.7 Watts 270 CFM/3.5 Sones (Horizontal) @ 0.10" SP. 150 CFM/1.1 Sones (Horizontal) @ 0.10" SP., 42.4 Watts

• **Dimensions** 

Overall bottom projection - 19½" Height -7½" Widths - 24", 30", 36"

# Hood Body

Stainless Steel or 24 gauge cold rolled steel, auto welded, powder coated

## • Motor

2 speed, thermally protected, permanently lubricated motor. Rated 120 volts, 60 hz. with two electronically balanced blower wheels.

### • Controls

Wall mounted dual rocker switch with plate, white finish. Fits into a triple gang box.

### • Lighting

Includes 26 Watt GU24 Base self ballasted lamp (bulb included) 4 watt night light (bulb not included)

### • Ducting Options


Horizontal ducting: 3¼"x10" (duct adapter and damper included) Vertical ducting: 3¼"x10" (duct adapter and damper included) Ductless\*: removable front vent (charcoal filter not included)

#### • Filters

Grease Filter: Dishwasher safe, GF-01 (included). Charcoal Filter: CF-01 (not included).

## • Available Finishes

Stainless Steel (ES248ADA, ES308ADA, ES368ADA) White (ES243ADA, ES303ADA, ES363ADA), Biscuit (ES244ADA, ES304ADA, ES364ADA), Almond (ES245ADA, ES305ADA, ES365ADA), Black (ES246ADA, ES306ADA, ES366ADA)



i di

**Compliant with ADA** (Americans with Dissabilities Act)



| EXPANDED PERFORMANCE    |                                  |     |       |      |     |      |        |           |       |      |  |
|-------------------------|----------------------------------|-----|-------|------|-----|------|--------|-----------|-------|------|--|
|                         | Static Pressure (inches of w.g.) |     |       |      |     |      | Sones  | Fan Speed | Power |      |  |
| Air Flow - CFM          | 0                                | 0.1 | 0.125 | 0.15 | 0.2 | 0.25 | @.1 SP | RPM       | Watts | Amps |  |
| Horz Ducting High Speed | 311                              | 270 | 261   | 251  | 225 | 188  | 3.5    | 1653      | 73.0  | 1.0  |  |
| Horz Ducting Low Speed  | 163                              | 150 | 144   | 137  | 66  | -    | 1.1    | 1229      | 42.4  | 1.0  |  |
| Vert Ducting High Speed | 310                              | 270 | 261   | 251  | 225 | 192  | 4.0    | 1653      | 73.0  | 1.0  |  |
| Vert Ducting Low Speed  | 159                              | 150 | 148   | 142  | 114 | 44   | 1.5    | 1189      | 42.7  | 1.0  |  |

| PROJECT<br>Location |                 |     |            |     |       |                         |  | ARCHITECT  |  |                         |  |  |
|---------------------|-----------------|-----|------------|-----|-------|-------------------------|--|--|--|-------------------------|--|--|
| CONTRACTOR          |                 |     |            |     |       |                         | SUBMIT                                   | ED BY  |  | DATE                    |  |  |
| FAN I<br>NUMBER N   | MODEL<br>IUMBER | CFM | IN<br>W.C. | RPM | WATTS | AMPS                    | SONES                                    | QTY  |  | AL EQUIPMENT<br>REMARKS |  |  |
| c<br>Intertek       | Us Churgy W     |     |            |     |       | er, Penns<br>2-7400 • 8 | nue<br>ylvania 19380-4466<br>77-304-3785 | Canada: 8 Edvac Drive<br>Brampton, Ontario L6S 5P2<br>Tel: (905) 456-2033<br>Fax: (905) 456-1015 |  |                         |  |  |

\* The ENERGY STAR Program for Residential Ventilating Fans has no provision for qualification of ductless rangehoods (recirculating not ventilating),

as a result the ENERGY STAR program applies to ducted rangehoods only. Specifications subject to change without notice.