





80 CFM/1.0 Sones @ 0.10" SP., 28.3 Watts 68 CFM @ 0.25 SP.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 11" x 13 3/4".

Blower Wheel

One piece polymeric centrifugal blower wheel, $5^{7/32}$ " diameter, $2^{29/32}$ " wide, with 30 paddles.

Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, suitable for continuous operation. Rated 120 volts, 60 hz.

Fan Housing

23 gauge galvanized steel housing. Dimensions: 107/8" x 93/8" x 77/8".

Humidity Sensor

Integrated humidity sensor automatically turns fan on until the desired humidity level is reached.

Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area


For bathrooms up to 80 sq. ft. For other rooms up to 100 sq. ft.

Electrical Connections

1/2" electrical knockouts provided.

Single Pack Shipping Info

Box Dim: 20" x 15¹⁵/16" x 11³/8" UPC: 0-8316228002-2 Shipping Weight: 17 lbs.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.





Unit Mounting

The housing will mount in ceilings with at least 8" of clearance and through drywall thickness up to 3/4", with a rough-in opening of $11^{1/8}$ " x 95/8". Rated for ceilings insulated to R-40. The housing will mount either between 16" or 24" on center joists, using the 4 supplied housing mounting rails. The housing mounting rails can be adapted for overhead mounting (hardware not provided).

EXPANDED PERFORMANCE												
								Sones	Sones	Fan Speed	Power	
	Static Pressure (inches of w.g.)							@ .1 SP	@ .25 SP	RPM	Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25					
Air Flow - CFM	87	83	80	78	77	72	64	1.0	1.0	975	28.3	0.31

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN Number	MODEL NUMBER	СҒМ	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	
1										







U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785 Fax: (610) 696-8048 Canada: 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 • 800-250-8767 Fax: (905) 456-1015

Specifications subject to change without notice.

Updated 3-12