

FOLD HERE AND
ALIGN TEMPLATE
ON HIGH EDGE OF
DOOR BEVEL.

FOLD HERE AND
ALIGN TEMPLATE
ON HIGH EDGE OF
DOOR BEVEL.

Test Fit Secondary Housing and Secondary Mounting Plate:
Prior to drilling the two lower 3/32" diameter holes, install the secondary mounting plate and test fit the secondary housing. Ensure the housing fits correctly over the mounting plate (the housing must be flush against the door and the top two housing trim screw holes must mate to their corresponding mounting plate trim holes). Adjust mounting plate as necessary.

**NOTE: DO NOT DRILL
THESE 3/32" HOLES
UNTIL SECONDARY
SIDE HOUSING IS
TEST FITTED**

METAL DOORS ONLY:
1/8" MIN. DEPTH HOLE
BOTH SIDES OF DOOR

**DL5200
DL5300
PDL5300**
Double-Sided
Locks



ALARM LOCK
345 Bayview Avenue
Amityville, New York 11701
For Sales and Repairs 1-800-ALA-LOCK
For Technical Service 1-800-645-9440
Publicly traded on NASDAQ Symbol: NSSC
© ALARM LOCK 2008

(DOOR THICKNESS)

(DOOR THICKNESS)

