Trilogy: Narrow Stile Access Locks

DL1200, DL1300, PDL1300 PIN and PIN/prox aluminum door retrofit outside trim

weatherproof

- **Aluminum door retrofit outside trim for Adams Rite**® 1850, 1950, 4710, 4070, 4730, 4900 Series and MS1850S and MS1950S Series latch locks.
- **Field-proven**, familiar Trilogy® programming & electronics
- **PIN code and PIN/Prox Models** support 100 to 2000 users (see model info.)
- **40,000 event audit trail** in 1300 Series models, provides door usage activity reports at wireless handheld printer, laptop or PC.
- **All-metal, vandal-resistant 12-button keypad** supports 3-6 digit PIN codes, and multilevel user hierarchy (master, manager, supervisor, basic users)
- **Keypad or PC programmable** (see model info.). Quickly and easily add or delete users and enter "passage mode", service codes, group lock-out & group-enable
- **HID Prox ID cards, keyfobs and prox tags supported** in PDL-1300 Series models featuring built in Prox reader. (High security applications can require use of both PIN code plus Prox ID for access.)
- **Real time clock and PC programmable automatic lock/unlock scheduling** for 500 events (1300 Series models).
- **Wide weatherproof operating range** from -31 to 151°F (-35 to 66C)
- **Wireless standalone locks:** Long-life, battery- operated; Includes audible and visual low battery alert. (Uses standard off-the-shelf batteries.)
- **Non-handed; fully field-reversible**
- **Key override; interchangeable cores supported** (Corbin/Russwin, Yale, Schlage, Medeco.)
- **Mortise Cylinder**, 1-1/4" supplied. (Supports 1-1/8, 1-1/4 and 1-3/8")
- **Compact styling** 14-3/8"H x 1-5/8"D x 1-3/4"W
- **Backsets** 31/32",1-1/8" and 1-1/2" ; **Stile thickness** 1-3/4"
- **Four attractive standard finishes** US26D Satin Chrome, US10B Duronodic, MS Metallic Silver and MB Metallic Bronze

Narrow Stile Trilogy® Lock models:

- **DL1200 Series** supports 100 users, fingertip/keypad programmable. (Includes 2 Lithium 3V batteries).
- **DL1300 Series** supports 2000 users and includes 40,000 event audit trail and 500 event schedule. Keypad or PC programmable. (Includes 2 Lithium 3V batteries) (See accessories below.)
- **PDL1300 Series** supports 2000 PIN or Prox users and includes 40,000 event audit trail and 500 event schedule. Keypad or PC programmable. (Includes 2 Lithium 3V batteries) (See accessories below.)
- **KIT ALSO AVAILABLE: Complete electronic and mechanical access retrofit kit** including Trilogy electronic narrow stile trim and mechanical Adams Rite 4900 Series dead latch lock (specify either 1 1/8" or 1 1/2" backset for mechanical lock required).

ORDERING: DL1200/26D1

Model Type
PDL – Prox/PIN
DL – Digital PIN
Trilogy Series
12 – 2700 Series
13 – 3000 Series
Trim
00 = Lever
25 = Turnpiece
50 = Knob
75 = Regal lever
Finish
/26D Satin Chrome
/10B Duronodic
/MS Metallic Silver
/MB Metallic Bronze

Mechanical Dead Latch
1 – Supports Adams Rite:
   4710, 4730, 4900 Series
2 – Supports Adams Rite:
   4070, MS1850S,
   MS1850S-050, MS1950,
   MS1950-050
3 – KIT Includes Adams Rite 4900 with
   1-1/8" backset, 628 &313 faceplate
4 – KIT Includes Adams Rite 4900 with
   1-1/2" backset, 628 & 313 faceplate

ⓊL CE

ALARM LOCK

There's a Trilogy keyless access lock for every requirement and application

MODEL:	DL12/1300	DL2700	DL2800	DL3000	DL4100	DL3500	DL4500	ETDL	DK3000
Lock Type	Narrow stile	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Mortise	Mortise	For Panic Trim	Keypad
Prox Reader model	PDL1300			PDL3000	PDL4100	PDL3500	PDL4500	ETPDL	PDK3000
Users	100 - 2000	17	200	DL3000 300; PDL3000 2000	2000	DL3500 300; PDL3500 2000	2000	2000	2000
Audit Trail	0 - 40000		1000	1600; 40000 (PDL)	40000	40000	40000	40000	40000
Schedules	0 - 500		150	150; 500 (PDL)	500	500	500	500	500
Privacy function					Yes		Yes		
Classroom/Deadbolt						CR or DB	DB		
Weather proof -31 to 151°F	Standard	WP version	Standard	WP version	Standard	Standard	Standard	Standard	Standard
Handing	Non	Non	Non	Non	Non	Field Reversible	Field Reversible	Non	
Std. Door Thickness	1-3/4"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	
Std. Backset	31/32", 1-1/8" 1-1/2"	2-3/4"	2-3/4"	2-3/4"	2-3/4"	2-3/4"	2-3/4"		
Cylinder or IC Prep	mortise, incdd	key in knob or 9 ICs	key in knob or 9 ICs	key in knob or 9 ICs	key in knob or 9 ICs	mortise, incdd	mortise, incdd	rim cyl., incdd	
Finishes (US)	26D, 10B, MS, MB	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26/D, 3, 5, 10B, MS, MB

ALARM LOCK