Bedrosians[®] Tile & Stone

Cool Blend - White Carrara, Nero Marquina & Bardiglio Nuvolato



100001697 Arlo Mosaic Blend - Honed (10 1/8"x15 7/8" Sheet)



100001699 Beckett Mosaic Blend - Honed (12 7/8"x11 3/4" Sheet)



100001710 Emery Mosaic Blend - Honed (13 5/8"x13 5/8" Sheet)



100001705 Jett Mosaic Blend - Honed (12"x12" Sheet)



100001707 Lennox Mosaic Blend - Honed (16"x16" Sheet)



100001709 Monroe Mosaic Blend - Honed (12"x12" Sheet)



100001701 Quin Mosaic Blend - Honed (11 5/8"x11 5/8" Sheet)



100001703 Zayden Mosaic Blend - Honed (12 5/8"x11 3/4" Sheet)

Warm Blend - Eastern White, Nero Marquina & Calcatta Zebrino



100001696 Arlo Mosaic Blend - Honed (10 1/8"x15 7/8" Sheet)



100001698 Beckett Mosaic Blend - Honed (12 7/8"x11 3/4" Sheet)



100001711 Emery Mosaic Blend - Honed (13 5/8"x13 5/8" Sheet)



100001704 Jett Mosaic Blend - Honed (12"x12" Sheet)



100001706 Lennox Mosaic Blend - Honed (16"x16" Sheet)



100001708 Monroe Mosaic Blend - Honed (12"x12" Sheet)



100001700 Quin Mosaic Blend - Honed (115/8"x115/8" Sheet)



100001702 Zayden Mosaic Blend - Honed (12 5/8"x11 3/4" Sheet)



Modni

Decorative (Marble Blend Mosaics)


Photo Features Quin Mosaic Blend - Honed in Warm Blend.

SIZING & PACKAGING

_							
Type	Shape	Cool Blend Item Code	Warm Blend Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Mosaic		100001697	100001696	101/8"x157/8" Sheet	Arlo Mosaic Blend - Honed	5	5.60
		100001701	100001700	115/8"x115/8"Sheet	Quin Mosaic Blend - Honed	10	9.30
		100001705	100001704	12"x12" Sheet	Jett Mosaic Blend - Honed	10	10.10
		100001709	100001708	12"x12" Sheet	Monroe Mosaic Blend - Honed	10	10.10
		100001703	100001702	125/8"x113/4" Sheet	Zayden Mosaic Blend - Honed	10	10.30
		100001699	100001698	127/8"x113/4" Sheet	Beckett Mosaic Blend - Honed	10	10.50
		100001710	100001711	135/8"x135/8"Sheet	Emery Mosaic Blend - Honed	10	12.90
		100001707	100001706	16"x16" Sheet	Lennox Mosaic Blend - Honed	5	8.85

ANSITECHNICAL SPECIFICATIONS

	Abrasion Resistance	Water Absorption	Average Bulk Specific Gravity	Compressive Strength Perpendicular (Dry)	Flexural Strength Perpendicular (Dry)	Modulus Rupture Perpendicular (Dry)
Results	11.98 lw	0.16	167.28 lbs/ft³ 2,680.6 kg/m³	13,000 psi	1,340 psi	1,500 psi
APPLICATIONS						
	Floors	Walls	Countertons	Shower Floors	Shower Walls	Pools/Spas



Shade Variation

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	• †	•	•	•†	•	
Commercial	• †	•	•	• †	•	

LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors

- Applications & ANSI Technical Specifications do not apply
- * Special Order only

Please be aware that white stones installed on shower floors may experience oxidization and rusting

All natural stone products must be sealed prior to grouting.

 $Do \ not \ use \ chlorine, a cids, or \ other \ harsh \ chemicals \ to \ clean. \ All \ spills \ must \ be \ cleaned \ immediately \ to \ prevent \ staining.$

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Natural stone has inherent variation in color/shade, size, texture, finish, veining, grain, movement and pitting. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Ensure proper installation, application, use, care and maintenance. Natural stone must be sealed prior to installation. Do not use aerosol catalyst adhesives. Only use pH neutral cleaners. Natural stone may experience changes in color and finish if installation and exterior application. There is no warranty for natural stone. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

100002559 REV. 2/2022