

Product details

COMPACT BLUMOTION hinge 3/4", 105°, with spring, hinge cup: press-in



| | |
|----------------------------|---------------|
| Part number | 38N358B.12 |
| Item number | 26294376 |
| Color / finish | Nickel-plated |
| Packaging quantity | 250 |
| Weight per 1,000 Pcs in kg | 44.65 |
| EAN code | 9002617889611 |
| UPC code | |

Technical attributes

| Attribute | Value |
|--|-------------------------------------|
| overlay in inches | 3/4 |
| opening angle | 105 |
| closing mechanism | with spring |
| hinge cup assembly | press-in |
| plate arm design and it's assembly | wrap around, no pre-hanging |
| hinge version | With integrated BLUMOTION |
| Depth adjustment | +2.6 / -0.6 mm |
| type of height adjustment | with elongated hole |
| Height adjustment | +/-3.2 mm |
| type of side adjustment | with cam |
| minimum boring distance | 2.5 |
| maximum boring distance | 3 |
| arm/plate arm mounting position | Mounting position 04 |
| hinge cup finish | Nickel-plated |
| hinge cup material | Steel hinge cup |
| Flange width | 57 |
| Flange length | 22 |
| Flange height | 2.5 |
| hinge cup depth | 11 |
| cup boring depth | 11 |
| diameter hinge cup boring | 35 |
| distance between borings | 45 |
| arm/plate arm finish | nickel-plated |
| eccentric location of mounting holes to hinge cup hole | 9.5 |
| functional length of dowel | 8.6x9.7 mm (overall length 11.4 mm) |
| collision measurement (hinge arm height) | 8.7 |
| arm/plate arm material | Steel |
| reveal | 4.8 |
| self closing start (degrees) | 30 |
| diameter of mounting holes | 8 |
| overlay in millimeters | 19 |
| Side Adjustment | +/-1.6 mm |

Product details

| Attribute | Value |
|--------------------------|--------------------|
| type of depth adjustment | with cam |
| item package | 1 piece |
| packaging | industrial packing |