

Product details

COMPACT CLIP hinge 1-1/4", 110°, with spring, mounting plate: with pre-mounted wood screw, hinge cup: press-in



| | |
|----------------------------|---------------|
| Part number | 31C358BS20 |
| Item number | 03616860 |
| Color / finish | Nickel-plated |
| Packaging quantity | 250 |
| Weight per 1,000 Pcs in kg | 90.82 |
| EAN code | 9009494511239 |
| UPC code | |

Technical attributes

| Attribute | Value |
|--|-------------------------------------|
| overlay in inches | 1-1/4 |
| opening angle | 110 |
| closing mechanism | with spring |
| hinge cup assembly | press-in |
| plate arm design and it's assembly | Wraparound |
| hinge version | With integrated BLUMOTION |
| Depth adjustment | + 2.3/- 0.6 mm |
| type of height adjustment | with cam |
| Height adjustment | +/- 2 mm |
| type of side adjustment | with cam |
| minimum boring distance | 2.5 |
| maximum boring distance | 3 |
| hinge cup finish | Nickel-plated |
| hinge cup material | Steel hinge cup |
| Flange width | 57 |
| Flange length | 22 |
| Flange height | 2.5 |
| hinge cup depth | 12.7 |
| cup boring depth | 12.7 |
| diameter hinge cup boring | 35 |
| distance between borings | 45 |
| eccentric location of mounting holes to hinge cup hole | 9.5 |
| functional length of dowel | 9.5x8.6 mm (overall length 11.4 mm) |
| collision measurement (hinge arm height) | 13 |
| reveal | 4.8 |
| self closing start (degrees) | 30 |
| diameter of mounting holes | 8 |
| overlay in millimeters | 31.5 |
| Side Adjustment | +/-1.6 mm |
| type of depth adjustment | with cam |
| item package | 1 piece |
| packaging | industrial packing |