


Submitted Model No.: \_\_\_\_\_

Specific Features: \_\_\_\_\_



# BRIZO®

## PERSONAL HAND HELD SHOWER

- Personal Hand Held Shower - Not a Positive Shut-Off
- 69" (1753 mm) Metal Hose
- Certified Dual Check Valves
- 24" (762 mm) Wall Bar with Slide (Model RP36003 only) Not to be used as a Grab Bar. Not ADA compliant.
- Wall Mount Hand Held Shower Bracket (Model RP36002 only)

### STANDARD SPECIFICATIONS:


- ABS hand held shower with three spray patterns - not a positive shut-off.
- 69" (1753 mm) flexible metal hose.
- Certified dual check valves.
- 24" (762 mm) wall bar with adjustable slide (allows for adjustable shower height) - RP36003 only. Not to be used as a Grab Bar. Not ADA compliant.
- Wall mount hand held shower bracket - RP36002 only.
- 2.5 gpm @ 80 psi (9.5 L/min @ 552 kPa)




### COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.3

### SPRAY PATTERNS



◆ Your Brizo® hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1 / CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.



Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only.

**Delta Faucet Company**  
 Indianapolis, Indiana 46280  
 A Division of Masco Corporation of Indiana  
 © 2007 Masco Corporation of Indiana