










The sculpted lines of Alta™ bring an exciting, new choice to typical range hood shapes. Sophisticated curves and hidden controls offer a beautiful alternative to traditional designs.


SIZE	BLACK	STAINLESS	WHITE	GREASE FILTERS (replacement)	NON-DUCTED FILTERS		
30 in.	ALT130BL	ALT130SS	ALT130WW	HPFAMM30 (Type "C1" / "C2")	HPF30 (Type "Xc")		
36 in.	ALT136BL	ALT136SS	ALT136WW	HPFAMM36 (Type "D1" / "D2")	HPF36 (Type "Xd")		

HVI PERFORMANCE										
		Damper	Sones			CFM				
Duct Orientation	Size		Normal	Medium*	High	Normal	Medium*	High 0.25 in. w.g.	High 0.1 in. w.g.	
Vertical - Rectangular	3¼ in. x 10 in.	Included	1.5	3.0	5.0	130	180	125	220	
Horizontal - Rectangular	3¼ in. x 10 in.	Included	1.5	3.0	5.0	110	150	115	210	
Round - Vertical	7 in.	Sold Separately	1.5	3.0	5.0	140	190	100	240	

300					
2-speed Rocker					
no					
no					
no					
yes					
2-level Halogen (included)					
Micro Mesh (Qty. 2)					
EZ1 Bracket					
no					
Non-ducted filters sold separately					
<b>AC INPUT</b> 120 V, 60 Hz - 1.4 AMPS					
OPTIONAL ACCESSORIES					
BP87Q					
MD6TU, MD8TU and MD10TU					
MOUNTING HEIGHT					
ooktop to bottom of hood					
ooktop to bottom of hood					







HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 and 0.25 in. static pressure at high speed based on tests conducted in an HVI-approved state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

\*Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.

99046183C

SPECIFICATION SHEET

<sup>\*\*</sup> Max. blower CFM indicates the performance of the hood blower in open air.