



Description:

Uni-plug design allows Ciro Down pendant to be mounted on any lighting system or ceiling canopy through the use of an appropriate adaptor, not included. Standard cable length of 59" can be field-cut or specified when ordering. May be specified with Kiss canopy by adding /MP to part number or /MP2 for 2" version.

Part Numbers:

220116bz	bronze, yellow and red glass
220116ch	chrome, yellow and red glass
220116mc	matte chrome, yellow and red glass
220119bz	bronze, white fritted glass
220119ch	chrome, white fritted glass
220119mc	matte chrome, white fritted glass
220121bz	bronze, gold-leaf glass
220121ch	chrome, gold-leaf glass
220121mc	matte chrome, gold-leaf glass
220122bz	bronze, red glass
220122ch	chrome, red glass
220122mc	matte chrome, red glass
220123bz	bronze, lava glass
220123ch	chrome, lava glass
220123mc	matte chrome, lava glass
220124bz	bronze, tan mosaic glass
220124ch	chrome, tan mosaic glass
220124mc	matte chrome, tan mosaic glass
220125bz	bronze, red mosaic glass
220125ch	chrome, red mosaic glass
220125mc	matte chrome, red mosaic glass

Technical Specs:

120V AC, 50/60Hz input
 11.7V AC output
 50VA. 49W for 1 (maximum 50 Watt lamp)
 GY6.35 socket
 Suitable for dry locations only
 Mount 3 1/2" - 4" round J-box
 Short circuit protection
 Overload protection

Thermal protection
Dimmable