



Description:

Uni-plug design allows Ciro Down pendant to be mounted on any lighting system or ceiling canopy through the use of an appropriate adaptor, not included. Standard cable length of 59" can be field-cut or specified when ordering. May be specified with Kiss canopy by adding /MP to part number or /MP2 for 2" version.

Part Numbers:

- 220116bz** bronze, yellow and red glass
- 220116ch** chrome, yellow and red glass
- 220116mc** matte chrome, yellow and red glass
- 220119bz** bronze, white fritted glass
- 220119ch** chrome, white fritted glass
- 220119mc** matte chrome, white fritted glass
- 220121bz** bronze, gold-leaf glass
- 220121ch** chrome, gold-leaf glass
- 220121mc** matte chrome, gold-leaf glass
- 220122bz** bronze, red glass
- 220122ch** chrome, red glass
- 220122mc** matte chrome, red glass
- 220123bz** bronze, lava glass
- 220123ch** chrome, lava glass
- 220123mc** matte chrome, lava glass
- 220124bz** bronze, tan mosaic glass
- 220124ch** chrome, tan mosaic glass
- 220124mc** matte chrome, tan mosaic glass
- 220125bz** bronze, red mosaic glass
- 220125ch** chrome, red mosaic glass
- 220125mc** matte chrome, red mosaic glass

Technical Specs:

- 120V AC, 50/60Hz input
- 11.7V AC output
- 50VA. 49W for 1 (maximum 50 Watt lamp)
- GY6.35 socket
- Suitable for dry locations only
- Mount 3 1/2" - 4" round J-box
- Short circuit protection
- Overload protection

Thermal protection
Dimmable