



Description:

The Ciro wall sconce may be mounted as an up-light or a down-light. The metal canopy and stem is available in bronze, polished chrome, and matte chrome plating. A 75W dimmable electronic transformer is included on the mounting plate.

Part Numbers:

| | |
|-----------------|------------------------------------|
| 100116bz | bronze, yellow and red glass |
| 100116ch | chrome, yellow and red glass |
| 100116mc | matte chrome, yellow and red glass |
| 100119bz | bronze, white fritted glass |
| 100119ch | chrome, white fritted glass |
| 100119mc | matte chrome, white fritted glass |
| 100121bz | bronze, gold-leaf glass |
| 100121ch | chrome, gold-leaf glass |
| 100121mc | matte chrome, gold-leaf glass |
| 100122bz | bronze, red glass |
| 100122ch | chrome, red glass |
| 100122mc | matte chrome, red glass |
| 100123bz | bronze, lava glass |
| 100123ch | chrome, lava glass |
| 100123mc | matte chrome, lava glass |
| 100124bz | bronze, tan mosaic glass |
| 100124ch | chrome, tan mosaic glass |
| 100124mc | matte chrome, tan mosaic glass |
| 100125bz | bronze, red mosaic glass |
| 100125ch | chrome, red mosaic glass |
| 100125mc | matte chrome, red mosaic glass |

Technical Specs:

- 120V AC, 50/60Hz input
- 11.7V AC output
- 50VA, 49W for 1(maximum 50 Watt lamp)
- GY6.35 socket
- Suitable for dry locations only
- Mount to 3 1/2" - 4" round J-box
- Short circuit protection
- Overload protection
- Thermal protection
- Dimmable