

Job Name:

Contact:

Fixture Type:

Part Number:



Description:

The Ledra R with J-box and Driver is a recessed fixture with a 70° tilt and 360° rotation on fixture head. Pressure fit mounting hardware allows for no screws to be visible. The small size, long life, lack of UV, rich color options, and cool beam allows for a wide variety of applications. Fixture includes a junction box and a driver. Ledra fixture is dimmable if used with appropriate Ledra dimming driver. Refer to a drive specification sheet for correct installation.

LEDRA® R WITH J-BOX AND DRIVER

Part Numbers:

i alt itallisers.	
135735bz/s	bronze, white, 10° lens
135735bz/m	bronze, white, 30° lens
135735bz/fl	bronze, white, 45° lens
135735mc/s	matte chrome, white, 10° lens
135735mc/m	matte chrome, white, 30° lens
135735mc/fl	matte chrome, white, 45° lens
135735wh/s	white, white, 10° lens
135735wh/m	white, white, 30° lens
135735wh/fl	white, white, 45° lens
135735-1bz/s	bronze, warm white, 10° lens
135735-1bz/m	bronze, warm white, 30° lens
135735-1bz/fl	bronze, warm white, 45° lens
135735-1mc/s	matte chrome, warm white, 10°lens
135735-1mc/m	matte chrome, warm white, 30°lens
135735-1mc/fl	matte chrome, warm white, 45°lens
135735-1wh/s	white, warm white, 10°lens
135735-1wh/m	white, warm white, 30°lens
135735-1wh/fl	white, warm white, 45°lens

Technical Specs:

100-240V AC, 50/60Hz input 700mA DC constant current output 6VA, 3W for 1 (3 Watt LED) White source of 140 lumens Warm White source of 120 lumens Suitable for dry locations only 2 1/4" hole cutout Required material thickness 3/16" - 1 1/16" Not thru-wire rated Short circuit protection

1 1 7/8" 1 1 1 1 7/8' 3 1 1

1 1/8"

1 1/4

Overload protection Thermal protection

Warranty:

All 3 Watt LED fixtures are warranted to be free from defects in material and workmanship for three (3) years from date of delivery.

For full warranty details, please see our terms and conditions <u>here</u>