

PRODUCT SPECIFICATION

Controlled Document - Engineering Drive

16/3 - 12/3

CATALOG NUMBER: See table below

> American Contractor® SJEOW extension cord with power indicator **DESCRIPTION:**

> > light in the cord connector

APPROVALS: UL Listed Outdoor Use Cord Set


CONSTRUCTION PARAMETERS:

Conductor: See table below TPE, yellow Cable jacket material:

Overall cable O.D. (nom): See table below Cord rating: Hard Usage per the National Electrical Code

Indent print

Cable legend type:





Attachment plug configuration: **NEMA 5-15P** Cord connector configuration: **NEMA 5-15R**

Plug and connector material: Clear PVC, with neon power indicator lamp in the cord connector

ELECTRICAL AND ENVIRONMENTAL PROPERTIES:

-50 to +90 °C Cable temperature rating: Nominal operating voltage: 125 VAC Maximum operating current: See table below

Catalog no.	Gauge	Length	Conductor	Cable O.D.	Current rating
01294	16/3	10 ft	26/30 BC	0.316 in	13A
01297		25 ft			
01298		50 ft			
01299		100 ft			10A
01497	14/3	25 ft	41/30 BC	0.352 in	15A
01498		50 ft			
01499		100 ft			13A
01697	12/3	25 ft	65/30 BC	0.420 in	15A
01698		50 ft			
01699		100 ft			
01798	10/3	50 ft	104/30 BC	0.567 in	
01799		100 ft			

This product complies with European Directive 2002/95/EC (RoHS)

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.

Coleman Cable Inc. 1530 Shields Drive, Waukegan, IL 60085 www.colemancable.com 800.323.9355