



A Division of Troy-CSL Lighting, Inc.

CounterAttack®

Project _____

Fixture Type _____

Voltage / Finish	WT	SS	BZ
120V Halogen	NCA-120-24 WT	NCA-120-24 SS	NCA-120-24 BZ
120V Xenon	NCAX-120-24 WT	NCAX-120-24 SS	NCAX-120-24 BZ

120V Line Voltage Xenon & Halogen



3 Lamp 24" (24" L x 5" W x 1½" H)

COUNTER ATTACK® FEATURES

Construction: Rolled steel, painted post manufacturing with molded plastic end caps.

Finish: Powder coat paint: White & Bronze or true Stainless Steel

Lens: Prismatic glass for even light distribution with UV coating

Lamps: Available in 35W 120V Halogen or 35W 120V Xenon G-8 Bi-pin base clear lamp. Halogen: 320 lumens @ 2,900K color temperature, 6,000 hour average rated life. Xenon: 270 lumens @ 2,650K color temperature, 9,000 hour average rated life.

Electrical: 120V hardwire only. No transformers remote or integral

Dimming: Dimming using 120V incandescent dimmer

Installation: Counter Attack easily comes apart with no tools required to enter the wire way. Large knockouts located every 6" on the back and top of the fixture and additional knockouts located on the sides. Once knockout has been removed, the fixture easily mount by use of captive screws pre-installed. Using wire nuts, connect 120V wires to wires within fixture, close fixture wire way and insert glass.

Listing: UL and cUL

Warranty: Counter Attach fixtures have a 1 year limited warranty from time of purchase from CSL



Removable hinged diffuser for easy and safe lamp replacement. Captive screws, fast installation.

MOUNTING & KNOCKOUTS
Counter Attack installs easily with two easy-to-access captive mounting screws. Fast, easy installation with multiple knockouts on ends, back and top for through-wiring, Wiremold, flex, Romex or rigid conduit.

Patented baffle increases the velocity of the cooling air.

Air space between fixture and mounting surface minimizes direct heat transfer and allows warm air to exhaust

Cooling air enters through slots around lens.

U.V Coated Prismatic Glass Diffuser, hinged door, no fasteners

Improved CounterAttack

Removable hinged diffuser; easy and safe lamp replacement

Captive screws: Easiest installation for under cabinet lighting

- 120V 35W Halogen and Xenon non-linking versions
- Longer lamp life than others due to patented cooling system
- Fast easy installation – complete with mounting hardware
- Knockouts on ends (non-linking only), back and top for through-wiring, Wiremold, flex, Romex or rigid conduit
- Repositioned cooling slots.
- Porcelain sockets used for high temperature durability
- Non-yellowing U.V. coated glass prismatic diffuser for maximum light distribution and U.V. protection
- Lamps included, no tools required for relamping
- Hi-Off-Lo switch, dimmable, energy saving
- Low profile fixture – 1½" high
- Available in white, stainless steel and bronze
- Protected by multiple US patents