

# LED Wall mount

The key design element of our LED wall mount is the removable lens. This feature allows for three distinctive styles during installation.



Model	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>LEDWALL-B</b>	29 W	2100 lm	2260 lm	90	3000 K	120 V - 277 V

### Specifications

Square housing made of extruded aluminum

Fixture canopy made of die-cast aluminum

LED module is mounted on an aluminum heat sink to maximize heat dissipation and extend product life

The square wall mount comes with 3 optical options:

- Bright aluminum reflector that provides a 45° beam spread
- Frosted glass lens to allow a wider beam spread
- Die-caster aluminum cap to allow a down only version

Compatible with TRIAC, ELV and 0-10 V dimmers

The LED board is sealed with a clear tempered glass lens to assure weatherproof operation

All components undergo a rigorous pre-treatment and are coated with a baked powder paint coat, giving them a highly durable finish

Warm white light output

Integrated dimmable driver

Title 24/JA8 certified

ENERGY STAR certified

ADA compliant

### Finish

**BK** Black

**SG** Silver grey

**WH** White

### Order example

#### **LEDWALL-B-SG**

LEDWALL-B square LED wall mount in a silver grey finish

### LEDWALL-B

