

2.0mm | 8 mil & 3.0mm | 20 mil
PINES TERRACE™
FLEXIBLE GLUE DOWN

PROSERIES™
LUXURY VINYL FLOORING
dalTile



SuperGuard™
REINFORCED SHIELD




2.0mm | 8 mil & 3.0mm | 20 mil PINES TERRACE™ FLEXIBLE GLUE DOWN

Create a design retreat with the transitional wood look visual in Pines Terrace. Offered in 7-1/4" x 48" planks, with embossed surfaces protected with SuperGuard™ Technology. Pines Terrace is the durable solution your project needs with the timeless style you want. Available in a 2.0 mm thickness and 8 mil wear layer for residential or multifamily unit applications and the commercial grade 3.0 mm thickness and 20 mil wear layer – both offered in five essential colors.

DESIGN RETREAT


- 7-1/4" x 48" wood look planks
- Five classic colors
- Flexible glue down
- Embossed texture
- 2.0 mm & 3.0 mm thickness options

Level 1

	Cardiology
	Pulmonology
	Radiology

SIMPLE SOLUTION

- SuperGuard™ Technology
- 8 mil & 20 mil wear layer for various traffic needs
- 100% Waterproof
- 100% Virgin Vinyl



2.0mm | 8 mil & 3.0mm | 20 mil
PINES TERRACE™
FLEXIBLE GLUE DOWN

SIZES:



7-1/4 x 48
Plank

7.25 x 48 WOOD LOOK PLANKS



BIRCH PT71 2 MM / 8 MIL
PT84 3 MM / 20 MIL



SUGAR PT60 2 MM / 8 MIL
PT73 3 MM / 20 MIL



GINGER PT65 2 MM / 8 MIL
PT78 3 MM / 20 MIL




CINNAMON PT66 2 MM / 8 MIL
PT79 3 MM / 20 MIL



WREATH PT69 2 MM / 8 MIL
PT82 3 MM / 20 MIL

INSTALLATION OPTIONS



BRICK



HERRINGBONE

2.0mm | 8 mil & 3.0mm | 20 mil
PINES TERRACE™
 FLEXIBLE GLUE DOWN



NOISE REDUCING



EASY TO CLEAN



100% WATERPROOF



100% VIRGIN VINYL

SPECIFICATIONS	2.0mm 8 mil	3.0mm 20 mil
Product Type:	LVF Dry Back	LVF Dry Back
Installation:	Glue Down	Glue Down
Thickness:	2.0 mm	3.0 mm
Wear Layer:	8 mil (0.2032mm)	20 mil (0.508mm)
Finish:	SuperGuard™ Technology	SuperGuard™ Technology
Size:	7.25" W x 48" L Plank	7.25" W x 48" L Plank
Underlayment:	N/A	N/A
Bevel:	N/A	N/A
Embossing:	Embossed	Embossed
Plank Variation:	5 Unique Planks	5 Unique Planks
Sq. Ft./Carton:	50.82	36.30
Pieces/Carton:	21	15
Weight	1.86lbs per pc/ 39.06 lbs per carton	2.51 lbs per pc/ 37.65 lbs per carton
Warranty:	Limited 20 Year Residential Warranty Limited 3 Year Multi Family Units Warranty	Limited 15 Year Commercial Warranty Limited 15 Year Multifamily Units Warranty Limited Lifetime Residential Warranty
Installation Advisory:	Glue Down LVF must be installed using ProSeries™ Adhesive by Daltile. See daltile.com/LVF for more recommended installation and adhesive information.	Glue Down LVF must be installed using ProSeries™ Adhesive and ProSeries™ High-Performance Adhesive by Daltile. See daltile.com/LVF for more recommended installation and adhesive information.
Stocking Platform:	2 mm 8 mil 3 mm 20 mil	
Special order Platform:	Additional Platforms available on special order. Minimum order quantities apply. Contact your Daltile representative for additional information.	

PERFORMANCE & CHARACTERISTICS

Construction:	Commercial Grade Luxury Vinyl Flooring; 100% Virgin Vinyl
Classification:	ASTM F1700 - Class III, Type B Embossed
Squareness:	ASTM F2421 - Passes - ±0.010" max
Size and Tolerance:	ASTM F2421 - Passes - Plank Length ≥ 48 in. ± 0.080 in. (2 mm)
Thickness:	ASTM F386 - Passes
Flexibility:	ASTM F137 - Passes - 1" mandrel
Dimensional Stability:	ASTM F2199 - Passes - 0.020 in./lin. Ft (0.51 mm/ 305 mm) maximum
Static Load Limit:	ASTM F970 - Passes
Residual Indentation:	ASTM F1914 - Passes - Average < 8.0% Max <= 10%
Resistance To Chemicals:	ASTM F925 - Passes - <= 1 Slight Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radian Flux:	ASTM E648- Passes -Class 1 (> 0.45w/cm²)
Smoke Density:	ASTM E662 Part A - Passes - < 450

NOTES

See daltile.com/LVF for recommended installation and care guidelines.



CERTIFIED BY
SCS Global Services

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com/LVF

PROSERIES™
LUXURY VINYL FLOORING



©2023 Dal-Tile, LLC (6/23)