













































Stone Usage Guide

At Daltile we understand how important it is to use the right stone for each project. Our extensive Stone Usage Guide has been developed to help you compare all products and choose the stone that best fits your project. Choosing the right product will ensure you enjoy your beautiful stone for many years to come.

For a side-by-side comparison within a collection, please click on the collection title below to view details.

[Granite](#) | [Limestone](#) | [Marble](#) | [Paredon](#) | [Quartzite](#) | [Sandstone](#) | [Slate](#) | [Stone a' la Mod](#)
[Stone Radiance](#) | [Travertine](#) | [Tumbled Natural Stone](#) | [Windowsills & Thresholds](#)

| Color # | Finish | Size/Thickness | Recommended Grout Joint | Durability Floor | Variation | Residential Exterior Usage | Commerical Exterior Usage | Special Notes |
|--|----------------|---|--|------------------|-----------|----------------------------|---------------------------|---|
| M313 Wedge | Polished | 2"x3"x3/8" (12"x13-3/8" sheet) | Approximately 1/16". No grout joint is recommended for High-Low, Random Split Face and Basket Weave. | 1 | M | EWS | EWS |     |
| M313 Linear | Polished | 5-3/4"x1/2"x3/8" (12"x13-3/8" sheet) | Approximately 1/16". No grout joint is recommended for High-Low, Random Split Face and Basket Weave. | 1 | M | EWS | EWS |     |
| M313 Oval | Polished | 1-1/2"x3/4"x3/8" (11-3/4"x12" sheet) | Approximately 1/16". No grout joint is recommended for High-Low, Random Split Face and Basket Weave. | 1 | M | EWS | EWS |     |
| M313 Mosaic | Polished | 1/2"x1/2"x3/8" (12"x12" sheet) | Approximately 1/16". No grout joint is recommended for High-Low, Random Split Face and Basket Weave. | 1 | M | EWS | |     |
| M313 High-Low Random Polished and Honed Contempo White | Polished/Honed | 2" High-Low Random x 1/4", 1/2", 3/8" (11-3/8"x11-3/8" sheet) | Approximately 1/16". No grout joint is recommended for High-Low, Random Split Face and Basket Weave. | 1 | M | EWS | EWS |     |
| M313 Basketweave Honed Contempo White | Honed | 1-1/2"x3/4"x3/8" (12"x12" sheet) | Approximately 1/16". No grout joint is recommended for High-Low, Random Split Face and Basket Weave. | 1 | M | EWS | EWS |     |
| M313 Random Brick-Joint Split Face Contempo White | Polished | 3/8" Random x 3/8" (11"x11" sheet) | Approximately 1/16". No grout joint is recommended for High-Low, Random Split Face and Basket Weave. | 1 | M | EWS | EWS |     |
| M313 High-Low Split Face Contempo White | Polished | 3/4"x3/4"x1/4" to 1/2" (12"x12" sheet) | Approximately 1/16". No grout joint is recommended for High-Low, Random Split Face and Basket Weave. | 1 | M | EWS | EWS |     |

| | | | | | | | |
|---|----------------|---------------------------------------|---|---|-------|-----|---|
| L222 Wedge Polished Urban Bluestone | Polished | 2"x3"x3/8" (12"x13-3/8" sheet) | Random Split Face and Basket Weave. Approximately 1/16". No grout joint is recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | M / H | EWS |  |
| L222 Linear Polished Urban Bluestone | Polished | 5-3/4"x1/2"x3/8" (12"x12" sheet) | recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | M / H | EWS |  |
| L222 Oval Polished Urban Bluestone | Polished | 1 1/2" x 3/4" x 3/8" | recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | M / H | EWS |  |
| L222 Mosaic Polished Urban Bluestone | Polished | 1/2" x 1/2" x 3/8" | recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | M / H | EWS |  |
| L222 High-Low Random Polished and Honed Urban Bluestone | Polished/Honed | 2" High-Low Random x 1/4", 1/2", 3/8" | recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | M / H | EWS |  |
| L222 Basketweave Honed Urban Bluestone | Honed | 1 1/2" x 3/4" x 3/8" | recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 4 | M / H | EWS |  |
| L222 Random Brick-Joint Split Face Urban Bluestone | Split Faced | 3/8" Random x 3/8" (11" x 11" sheet) | recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | M / H | EWS |  |
| L222 High-Low Split Face Urban Bluestone | Split Faced | 3/4" x 3/4" x 1/4" to 1/2" | recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | M / H | EWS |  |
| M312 Wedge Polished Nouveau Nero | Polished | 2" x 3" x 3/8" | recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | L | EWS | EWS  |
| M312 Linear Polished Nouveau Nero | Polished | 5 3/4" x 1/2" x 3/8" | recommended for High-Low, Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | L | EWS | EWS  |

| | | | | | | | | |
|--|----------------|---|---|---|---|-----|-----|---|
| M312 Oval Polished Nouveau Nero | Polished | 1 1/2" x 3/4" x 3/8" | recommended for High-Low , Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | L | EWS | EWS |     |
| M312 Mosaic Polished Nouveau Nero | Polished | 1/2" x 1/2" x 3/8" | recommended for High-Low , | 1 | L | EWS | EWS |     |
| M312 High-Low Random Polished and Honed Nouveau Nero | Polished/Honed | 2" High-Low Random x 1/4", 1/2", 3/8" | recommended for High-Low , Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | L | EWS | EWS |     |
| M312 Basketweave Honed Nouveau Nero | Honed | 1 1/2" x 3/4" x 3/8" | recommended for High-Low , Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | L | EWS | EWS |     |
| M312 Random Brick-Joint Split Face Nouveau Nero | Split Faced | 3/8" Random x 3/8" | recommended for High-Low , Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | L | EWS | EWS |     |
| M312 High-Low Split Face Nouveau Nero | Split Faced | 3/4" x 3/4" x 1/4" to 1/2" | recommended for High-Low , Random Split Face and Basket Weave. Approximately 1/16". No grout joint is | 1 | L | EWS | EWS |     |
| M314 Block Random Polished Upton Blend | Polished | Block Random Blend x 3/8" (12" x 12" sheet) | recommended for High-Low , Random Split Face and Basket Weave. | 1 | L | EWS | EWS |     |


Durability Legend

1. Residential: Suitable for residential use. Not recommended for commercial areas.
2. Medium/Light Commercial: Suitable for light commercial and residential use.
3. Heavy Commercial: Suitable for most commercial and/or high traffic areas.







Color Variations Legend

- L Low : Background color is relatively uniform.
- M Medium: Background color contains light variations.
- H High: Background color contains distinct variations.
- R Random: Variegated in color and veining. Blending allowances during installation are strongly recommended.

Exterior Usage Legend

-  Suitable for exterior application in freezing and non-freezing climates.
- EF Suitable for covered exterior floors in freezing and non-freezing climates.
- EW Suitable for covered exterior walls in freezing and non-freezing climates.
- EC Suitable for covered exterior countertops in freezing and non-freezing climates.

Special Notes Legend

-  Not recommended in wet areas.
-  Can be used in interior wet areas, if sealed and maintained properly. If not properly maintained, the stone look could be altered. Please contact your sealer manufacturer or your Daltille sales representative for information about products that can protect the stone from moisture exposure.
-  Might contain dry seams, pits, fossils, and glass veins that are filled at the factory or during installation. These are all inherent characteristics of the stone. Since these voids can sometimes lose their fillings, they should be refilled as part of normal maintenance.
-  A sealer is recommended. (Note: Some sealers are not recommended for use on certain stone types.)
-  These stones contain deposits or inclusions that are not recommended for use in certain applications.
-  White thin-set or mortar is recommended.

limestone and tumbled stone should be sealed prior to grouting.)

minerals and iron that may react to moisture. Stone bleeding or rusting is a common example of this. These stones should not be used in installations where they would be exposed to standing, run off water or too much humidity. A sealer is strongly recommended but will not prevent the chemical reaction from happening. Please contact your sealer manufacturer for information about products that can protect the stone from moisture exposure.



Install with a non-staining epoxy. Do not use any water based setting material with these stones.