

# PORCEALTO™ colorbody™ porcelain



behind the Porcealto collection. With earthen textures, fails to provide an added depth to your space.

Nothing is more inspiring than running warm sand through your fingers - and such organic beauty was the inspiration whether fine or coarse, solid or smooth - Porcealto never



# PORCELATO™ colorbody™ porcelain

## Field Tile - Graniti Series (Fine Grain Series)



<sup>\*</sup>A grid (skid-resistant) surface finish is available via special order in 8 x 8 only in select colors. (1), (2), (3) and (4) indicate Price Group, (1) being the least expensive. See chart for size and surface availability.

## Field Tile - Solids







#### SIZES - SOLIDS (Stocked)

		SQ.FT. CARTON	PCS. PER CARTON
12 x 12 Field Tile (Unpolished)	(11-13/16" x 11-13/16") (30.0 cm x 30.0 cm)	15.00	15
4 x 4 Field Tile* (Unpolished)	(3-15/16" x 3-15/16") (10.0 cm x 10.0 cm)	9.47	88

<sup>\*</sup>Not available in CD28 Bianco Ghiaccio

#### SIZES - GRANITI & GRANI

		SQ.FT. CARTON	PCS. PER CARTON
12 x 12 Field Tile	(11-13/16" x 11-13/16") (30.0 cm x 30.0 cm)	15.00	15
8 x 8 Field Tile (Graniti only)	(7-13/16" x 7-13/16") (18.3 cm x 18.3 cm)	13.30	30

Graniti & Grani sizes are available in Polished, Unpolished and Textured.

#### SIZES - SPECIAL ORDER\*\*

		SQ.FT. CARTON	PCS. PER CARTON
12 x 12 Field Tile (Polished)	(11-13/16" x 11-13/16") (30.0 cm x 30.0 cm)	15.00	15

<sup>\*\*</sup>Not available in CD01 White

#### **RESIDENTIAL USAGE**

FLOORS	WALLS	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	$\bigvee$	С	EP***	ED*

<sup>\*\*\*</sup>Unpolished and textured surfaces only.

#### **COMMERCIAL USAGE**

	INTERIOR			EXTERIOR		
	RESIDENTIAL	LIGHT COMMERCIAL	. COMMERCIAL	RESIDENTIAL	COMMERCIAL	
Floors/Patios	<b>✓</b>	<b>✓</b>	✓▼	✓▼	<b>/</b> †	
Walls/Backsplashes	<b>✓</b>	~	<b>~</b>	~	<b>✓</b>	
Countertops	<b>✓</b>	~	<b>✓</b>	~	<b>✓</b>	
Pool Decking <sup>†</sup>	<b>✓</b>	~	<b>✓</b>	~	<b>✓</b>	
Pool Linings	<b>✓</b>	<b>✓</b>	<b>✓</b>	~	<b>✓</b>	

Suitable for freezing and non-freezing climates when proper installation methods are followed.

#### SHADE VARIATION





LOW (VI) Monochromatic consistent color within each tile, and from tile to tile. (Solids)

#### INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
5/16"	1/4"

#### SLIP RESISTANCE (WET): 3

The higher the rating, the higher the slip resistance.

ī	: .50	
2	5059	
3	: .60	_

#### **TEST RESULTS**

	ASTM#	Flo	or Result
Vater Absorption	6373	Unpolished Polished	< 0.5%
olids/Graniti/Grani	C373	Textured	< 0.5% < 0.5%
reaking Strength	C648	Unpolished	
rani	C0+0	Polished	> 497 lbs
eaking Strength		Unpolished	
lids/Graniti	C648	Polished	
ids/ Grainer		Textured	> 520 lbs
ratch Hardness	MOHS	Unpolished	7.5
rani	MOHS	Polished	7.5
		Unpolished	7.5
Scratch Hardness Solids/Graniti	MOHS	Polished	7.5
.ds/Graniti		Textured	8.0
emical Resistance	C650	All	Resistant
namic C.O.F.	41271	Unpolished	≥ 0.42
ani	A137.1	Polished	≥ 0.42
		Unpolished	≥ 0.42
namic C.O.F. lids/Graniti	A137.1	Polished	≤ 0.42
		Textured	> 504 lbs > 497 lbs > 497 lbs > 497 lbs > 520 lbs 7.5 7.5 7.5 8.0 Resistant ≥ 0.42 ≥ 0.42

#### **NOTES**

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: www.daltile.com/CommercialFactors

Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

<sup>▲</sup> Textured surface only.

<sup>▼</sup> Unpolished and textured surfaces only.

<sup>†</sup> Textured surface only.

#### **SOLID SERIES - COLORS**

### GRANITI SERIES - (FINE GRAIN) COLORS

	4 x 4 Unpolished	12 x 12 Unpolished	12 x 12 Polished
CD01	STK	STK	N/A
CD02	STK	STK	SP
CD03	STK	STK	SP
CD04	STK	STK	SP
CD19	STK	STK	SP
CD20	STK	STK	SP
CD21	STK	STK	SP
CD24	STK	STK	SP
CD25	STK	STK	SP
CD28	N/A	STK	SP
CD47	STK	STK	SP
CD48	STK	STK	SP
CD83	STK	STK	SP
CD85	STK	STK	SP

	8 x 8 Unpolished	8 x 8 Textured	12 x 12 Unpolished	12 x 12 Polished	12 x 12 Textured
CD05	STK	SP	STK	STK	STK
CD07	STK	N/A	STK	SP	N/A
CD31	STK	SP	STK	STK	STK
CD37	STK	N/A	STK	STK	N/A
CD38	STK	N/A	STK	STK	N/A
CD39	STK	N/A	STK	STK	N/A
CD40	STK	N/A	STK	STK	STK
CD4I	STK	SP	STK	STK	STK
CD42	STK	SP	STK	STK	SP
CD49	STK	N/A	STK	SP	N/A
CD56	STK	N/A	STK	STK	N/A
CD77	STK	N/A	STK	SP	N/A
CD78	STK	N/A	STK	SP	N/A
CD98	STK	N/A	STK	STK	N/A

#### **SOLID SERIES - TRIM**

	S-4449 4 x 4 SBN	SCRL-4449 4 x 4 Corner	S-36C9T 6 × 12 CV BS	SC-3689T I x 6 CV Out	S-44C9 4 × 12 SBN
CD0I	SP	SP	STK	STK	STK
CD02	SP	SP	STK	STK	STK
CD03	SP	SP	STK	STK	STK
CD04	SP	SP	STK	STK	STK
CD19	SP	SP	STK	STK	STK
CD20	SP	SP	STK	STK	STK
CD21	SP	SP	STK	STK	STK
CD24	SP	SP	STK	STK	STK
CD25	SP	SP	STK	STK	STK
CD28*	N/A	N/A	STK	STK	STK
CD47	SP	SP	STK	STK	STK
CD48	SP	SP	STK	STK	STK
CD83	SP	SP	STK	STK	STK
CD85	SP	SP	STK	STK	STK

 $<sup>*</sup>I \times 6$  Cove Corner is SC-36C9T

### GRANITI SERIES - (FINE GRAIN) TRIM

	S-4489 4 x 8 SBN	SCR-4489 SCL-4489 4 x 8	S-3689T 6 × 8 CV Base	SB-3689T I x 6 CV In	SC-3689T I x 6 CV Out	S-44C9 4 × 12 SBN	12 x 12 Stair Tread	8 x 8 Grid
CD05	STK	STK	STK	STK	STK	STK	SP	SP
CD07	STK	STK	STK	STK	STK	STK	SP	N/A
CD31	STK	STK	STK	STK	STK	STK	SP	SP
CD37	STK	STK	STK	STK	STK	STK	N/A	N/A
CD38	STK	STK	STK	STK	STK	STK	N/A	N/A
CD39	STK	STK	STK	STK	STK	STK	N/A	N/A
CD40	STK	STK	STK	STK	STK	STK	SP	N/A
CD4I	STK	STK	STK	STK	STK	STK	SP	SP
CD42	STK	STK	STK	STK	STK	STK	SP	SP
CD49	STK	STK	STK	STK	STK	STK	SP	N/A
CD56	STK	STK	STK	STK	STK	STK	SP	N/A
CD77	STK	STK	STK	STK	STK	STK	N/A	N/A
CD78	STK	STK	STK	STK	STK	STK	N/A	N/A
CD98	N/A	N/A	STK	STK	STK	STK	N/A	N/A

## PORCEALTO™

## COLORBODY™ PORCELAIN







By their very design, Daltile products can help make it easier for you to earn LEED<sup>10</sup> points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit daltilegreenworks.com.









