


ATHENA MOSAICS™

MOSAIC

Professional

SOLIDS





Stone Gray AH09 I/2" x I/2"

Suede Grav AH21

Suede Gray AH21 1/2''×1/2''




Black AH 15 1/2" × 1/2"




Professional

MOSAIC

BLENDS



Match Point AH34 I/2" x I/2"



Cactus Hill AH40 1/2" × 1/2"



Iron Gate AH38 1/2'' × 1/2''




Autumn Harvest AH37 1/2" × 1/2"




Nautical Breeze AH36 1/2" x 1/2"



Toasted Almond AH35 1/2" × 1/2"



Pacific Mist AH39 1/2" x 1/2"



Coral Soiree AH41 1/2" x 1/2"

Sizes

		Nominal	Sq. Ft. per carton	Sheets per carton
33811386138611381	'2'' Field Tile nounted)	(Sheet Nominal 11-3/4" x 11-3/4") (Sheet Nominal 29.85 cm x 29.85 cm)	10.00	10
Installation				
Thickness	G	rout Joint Recommendation	Shade Va	riation
1/4"		1/8" Approximately	Lov	v (VI)

Notes

Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A I 37.1 standards.

Application

	Residential	Light Commercial	Commercial	Commercial Exteriors
Floors	Bathrooms only	* **		
Walls/Backsplashes	*	*	*	*
Countertops*	*	*	*	
Pool Decking				
Pool Linings	*	*	*	*

Suitable for exterior walls in freezing and non-freezing climates when proper installation methods are followed. Not for use on shower floors.

Test Results

	ASTM#	Result	
Water Absorption	C373	<0.5%	
Breaking Strength	C648	>350 lbs	
Scratch Hardness	MOHS	6.0-7.5	
Chemical Resistance	C650	Resistant	
Coefficient of Friction	C1028	Dry: ≥0.70	
Abrasion Resistance	C1027		

For additional information refer to "Factors to Consider" at: www.daltile.com/CommercialFactors

Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.



^{*}Darker colors on counters may show scratches.

^{**}Office building restroom floors and hotel baths only. Not for use on shower stall floors.