


Submitted Model No.:\_\_\_\_

**Specific Features:** 



### ▲ Designate Proper Finish Suffix

Your Delta Faucet hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3, CSA B125.1 and ASME A112.18.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.



# ROMAN TUB/WHIRLPOOL FAUCET TRIM

- Ara<sup>™</sup> Bath Collection
- Three Hole Installation (T2768 Series)
- Four Hole Installation (T4768 Series)
- Rough-In Kit Must Also be Ordered to Complete Installation (R4707 for four hole and R2707 for three hole)

#### **STANDARD SPECIFICATIONS:**

- Trim Only for two handle Roman Tub faucet for concealed mounting.
- 9" (229 mm) long, 6 11/16" (170 mm) high slip-on rigid spout.
- Temperature and volume controlled with handles.
- Red/blue button covers on handle for hot/cold identification.
- Rough-In kit must also be ordered to complete installation (R4707 for four hole and R2707 for three hole). There are separate specification sheets on each rough-in kit if more details are required.
- Handshower includes double check valves for backflow prevention (T4768).
- H<sub>2</sub>Okinetic<sup>®</sup> Handshower water efficient flowrate of 2.0 GPM @ 80 PSI.

#### WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

## **COMPLETE VALVE COMPLIES WITH:**

■ ASME A112.18.1 / CSA B125.1 ◆ Indicates compliance to ICC/ANSI A117.1

