

▲ Designate proper finish suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



■ 2-In-1 Shower

STANDARD SPECIFICATIONS:

- Maximum 2.5 GPM at 80 PSI, 9.5L/min @ 552 kPa
- Integrated handshower docks securely into showerhead when not in use.
- Multiple handshower spray setings and pause feature.
- 60" 82" stainless steel stretchable hose.
- 72" plated ribbon hose.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

■ ASME A112.18.1/CSA B125.1◆

◆ Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, nonserviceable parts of the wand assembly.



55 E. 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2015 Masco Corporation of Indiana