

( DELTA
---------

# LAVATORY FAUCETS

- Windemere® Collection
- Two Handle Deck Mount

### Min. 2 1/2" (64 mm) Clearance to Back Splash Recommended 9 1/2" 5 1/8' (241mm) (130 mm) 5 7/8" (149mm) 3 5/8' 3 17/32" (92mm) (90 mm) 1/2" - 14 NPSM 3 X 1"~1 1/2" (25~38 mm) (102mm) → Hole Size 2 3/8" 1 1/8"-Centers (61mm) (29mm) Max. Deck 6 1/8" Thickness (156mm) 2 1/8" (54 mm) Dia. 1 5/8" (42 mm) to 2 3/8" 3 1/2" (61 mm) 1 3/8" (89 mm) <sup>[</sup> (35 mm) Dia. 4 5/8" (118 mm) 1 1/4" (32 mm)

▲ Designate proper finish suffix

## **STANDARD SPECIFICATIONS:**

- Maximum 1.5 qpm @ 60 PSI, 5.7 L/min @ 414 kPa
- Three hole mount
- 1/4 turn stops
- Control mechanism is a rotating cylinder type with stainless steel plate and 90° rotation, with replaceable non-metallic seats
- Models include metal pop-up type fitting with plated metal flange and stopper cap

#### **WARRANTY**

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



## **COMPLIES WITH**

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2

Indicates compliance to ICC / ANSI A117.1

■ EPA WaterSense®

Verified compliant with 0.25% weighted average Pb content regulations.



55 E. 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2015 Masco Corporation of Indiana