

Designate proper finish suffix

SPRAY PATTERNS

Spray w/Massage



H2Okinetic[®] PowerDrench[®] Spray





Pause



see what Delta can do

IN2ITION[®]

- H₂Okinetic[®] 2-In-1 Shower
 4-Spray Settings Hand Shower
- Push Button Selection
- MagnaTite[®] Docking

STANDARD SPECIFICATIONS:

- Maximum 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa
- Integrated hand shower docks securely into shower head when not in use
- 4 hand shower spray settings pause is a nonpositive shut-off
- 3-Way diverter for single or shared operation of the shower head and hand shower
- Fixed shower head and hand shower all in one
- Change spray modes with push button
- 60" (1524 mm) stretchable metal hose, stretches to 82" (2083 mm) for extra reach

WARRANTY

- · Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

ASME A112.18.1 / CSA B125.1 ASME A112.18.3

◆ Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certifled check valves in series, which operate independently and are integral, nonserviceable parts of the wand assembly.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.