


Submitted Model No.:

Specific Features:



#### ▲ Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.



# AVATORY **FAUCETS**

- Lahara<sup>®</sup> Bath Collection DIAMOND Seal<sup>®</sup> Technology
- Single Handle Deck Mount
- 1 or 3 Hole Mount

(Optional 6 1/2" Escutcheon Included)

Touch<sub>2</sub>O<sub>.xt</sub><sup>™</sup> Technology

### STANDARD SPECIFICATIONS:

- Single handle lavatory deck faucet.
- 1 or 3 hole mount (6 1/2" (165 mm) escutcheon plate included).
- 5 1/2" (140 mm) long spout.
- 1 1/8" minimum 1 1/2" maximum hole size.
- Lever handle. Control mechanism is the diamond embedded ceramic disc cartridge.
- Control handle shall return to neutral position when valve is turned off.
- 3/8" O.D. straight, staggered pex supply tubes 35" (889 mm) and 36" (914 mm) long.
- Maximum 1.5 gpm flowrate @ 60 PSI.
- Models include polypropylene pop-up.
- Delta Touch<sub>2</sub>O.<sub>xt</sub>™ Technology or proximity sensing technology controls water flow.
- Blue light flashes for proximity activation and solid blue for touch activation.
- On-Off indicator light signals when batteries are low.
- Uses 4 AA batteries (included).

#### WARRANTY

 5 Year Limited Warranty on faucet, finish and electronics.








## **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1ASME A112.18.2 / CSA B125.2

Indicates compliance to Indicates co...

 Verified compliant with .25% weighted average Pb content regulations.





55 E. 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2011 Masco Corporation of Indiana