








# Delta BreezGreenBuilder Ventilation Fan / Light Combo Specifications

**GBR100L** (100 CFM)







## Description

Low noise ceiling mount ventilating fan rated for continuous running. Fan has been awarded ENERGY STAR® Most Efficient in 2013. It is HVI, UL, and cUL certified, and can be used to comply with ASHRAE 62.2 (intermittent operation), CA Title 24, and CALGreen requirements.

#### Motor/Blower

- Power rating of 120volts/60Hz
- DC brushless motor engineered to run continuously
- · Motor equipped with thermal cutoff fuse
- · Permanently lubricated motor

## Housing

- · Galvanized steel body
- Detachable 4" diameter duct adapter
- · Built-in backdraft damper
- · Easy installation

#### Grille

- Attractive design using ABS material
- · Attaches directly to housing with included grille bracket

## Light

· 26-Watt GU24 CFL

## **LED Indicator**

• Turn the power switch on/off to operate on/off. LED indicator will be green when power is on

# Warranty

· 3-year limited warranty

## **Features**

- For ceiling mount only, air flow of 100 CFM (±10%) and 1.4 sones at 0.1" static pressure
- Power consumption approximately 13.9 Watts with an efficiency rating approximately 7.1 CFM/Watt at 0.1" static pressure
- UL and cUL listed for tub/shower enclosure when used with GFCI-protected branch circuit wiring

### DC Motor Technology

- Built-in soft start function to increase bearings' life
- · Automatically powers off when the impeller is locked abnormally

## **Specifications**

GBR100L	4" Duct (Standard)	
Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	100	76
Sones	1.4	1.3
Power Consumption (Watts)	13.9	11.9
Energy Efficiency (CFM/Watt)	7.1	6.3
Current (Amps)	0.23 Max	
Power Rating (V/Hz)	120 / 60	
Lamp (Watts)	26	







