


## Commercial Fan Forced Heater

Solutions for maintaining comfort in areas subject to cold drafts, such as vestibules, stairwells etc.



RFF Series



RFI Series



RFV Series



RFITF T-bar Ceiling Mount Trim (white only)

### Features

- Quick response of fan-forced heat when required
- Automatic fan delay to remove residual heat when unit cycles off
- Recessed or surface mounting ceiling or wall
- 50/60 cycle rating
- Exclusive aesthetically pleasing front panel trim
- Access door can be locked for tamperproof applications on RFI model

### Applications

- Vestibules, entrance ways, stairwells, kiosks

### Specifications

<b>Voltage</b>	208, 240, 347, 600V
<b>Wattage</b>	Nine sizes ranging from 1125 to 8000W
<b>Colour</b>	Almond or White
<b>Finish</b>	Polyester epoxy powder coat painted finish.
<b>Construction</b>	The front panel is constructed of 20 gauge steel. The wall box is designed for recessing into either frame or masonry walls and contains knockouts for wiring connections.
<b>Heating element</b>	The RFI/RFV/RFF wall heater has a nickel chromium resistance wire heating element within a steel sheath. Spiral steel fins are firmly brazed to the surface to provide excellent heat transfer.
<b>Motor &amp; Fan</b>	The fan motor is totally enclosed and factory lubricated complete with a black anodized 5 blade mixed flow aluminum fan. The fan delay is a bi-metallic snap action type.
<b>Controls &amp; wiring</b>	208V and 240V units have a standard double pole built-in thermostat with provision for a remote wall stat if required. 347V and 600V units have a built in thermostat. Use low voltage relay kits and suitable wall mount thermostat for remote temperature control.
<b>Warranty</b>	One year on complete unit. UL and CSA approved.



**Ordering Guide**

Cat. No.	Watts	BTU	Volts	Phase	CFM	Weight kg/lbs.
RFI815D31	1500/1125	5118/3840	240/208	1	160	12.7/28.0
RFI820D31	2000/1500	6824/5118	240/208	1	160	12.7/28.0
RFI830D31	3000/2250	10236/7680	240/208	1	160	12.7/28.0
RFI840D31	4000/3000	13648/10236	240/208	1	160	12.7/28.0
RFI840D21	4000	13648	208	1	160	12.7/28.0
RFI848D31	4800/3600	16378/12283	240/208	1	160	12.7/28.0
RFV831551	3000/1500	10236/5118	347	1	160	16.0/34.0
RFV831581	3000/1500	10236/5118	600	1	160	16.0/34.0
RFV842051	4000/2000	13684/6824	347	1	160	16.0/34.0

Cat. No.	Watts	BTU	Volts	Phase	CFM	Weight kg/lbs.
RFV842081	4000/2000	13684/6824	600	1	160	16.0/34.0
RFF86021	6000	20472	208	1	320	30.0/65.0
RFF86031	6000	20472	240	1	320	30.0/65.0
RFF86051	6000	20472	347	1	320	36.0/80.0
RFF86081	6000	20472	600	1	320	36.0/80.0
RFF88021	8000	27296	208	1	320	30.0/65.0
RFF88031	8000	27296	240	1	320	30.0/65.0
RFF88051	8000	27296	347	1	320	36.0/80.0
RFF88081	8000	27296	600	1	320	36.0/80.0

**Control Accessory Kits (field installed)**

Cat. No.	Description
RFLVC21	208V 22A low volt relay w/ 24V transformer kit for RFI
RFLVC31	240V 22A low volt relay w/ 24V transformer kit for RFI
RFLVD	208-240V low volt relay kit only for RFI series
RFVLVC51	347V low volt relay w/ 24V transformer kit for RFV
RFVLVC81	600V low volt relay w/ 24V transformer kit for RFV
RFVLVD	347-600V low volt relay kit only for RFV series

**Control Options (factory installed)**

Cat. No.	Description
RFFLVD	208-600V low volt relay only for RFF series
RFFLVC	347-600V low volt relay w/ 24V transformer for RFF

**Accessories (field installed)**

Cat. No.	Description
RFP8DA	Surface mount box for RFI/RFV series (almond) 425mm x 546mm x 97mm (16.8" x 21.5" x 3.8")
RFP8DW	Surface mount box for RFI/RFV series (white) 425mm x 546mm x 97mm (16.8" x 21.5" x 3.8")
RFFP8CA	Surface mount box for RFF series (almond) 832mm x 546mm x 97mm (32.8" x 21.5" x 3.8")
RFFP8CW	Surface mount box for RFF series (white) 832mm x 546mm x 97mm (32.8" x 21.5" x 3.8")
RFITF	T-Bar ceiling frame for RFI/RFV series (white only)
RFIBGA	Tamperproof bar grill (almond)
RFIBGW	Tamperproof bar grill (white)

**Dimensions**

