

Project name:	
Fixture type:	

Date:

4" Reflector Trim



Features

- · Reflector Trim.
- Lamp: 32W max CFL (PL-T), 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- O.D.: 5"

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options







All White

Clear w/White Ring

All Bronze







Haze w/White Ring

All Gold

Gold w/White Ring








Black w/White Ring

All Black

Clear w/Nickel Ring

Dimensions



Product Number

Item	Finish
EL999H	Haze w/White Ring

Product Number Builder Example: EL999BZ

4" Reflector Trim	Finish
EL999	
	BZ All Bronze
	W All White
	B Black w/White Ring
	C Clear w/White Ring
	G Gold w/White Ring
	H Haze w/White Ring
	BB All Black
	CN Clear w/Nickel Ring
	GG All Gold

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**



4" Airtight IC Housing **New Construction**

CAI NO.	
EL99ICA	

SPECIFICA	HONS	
amp: 50W	/ MAX	

CAT NO.	
EL99A	

CAT NO.	SPECIFICATIONS
L99A	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
FL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing Remodel



4" Housing Remodel



4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99RICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
FI 99RA	Lamp: 50W MAX

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	



4" Airtight IC Housing with GU24 Base Socket **New Construction**



4" Airtight IC Housing with GU24 Base Socket Remodel

CAT NO.	SPECIFICATIONS
FI 99ICΔ-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS
FI 99RICΔ-G24	Lamp: 18W MAX.

4" Accessories



Fire Cover

)	
1	K L
3	1
2)	

Fire Enclosure



CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS
FIRECVR	TINELINGE	FIREENCL	20 %" L x 14 %" W
		FIREENCL-S	Shallow, 16" L x 14 %" W

Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	³⁄4″ W × 16′ L