

Project name:	
Fixture type:	
Date:	

4" Shower Trim with Albalite Lens



Features

- Shower Trim with Albalite Lens.
- Lamp: 32W MAX CFL (PL-T) or 30W MAX R20.
- O.D.: 4 3/4"


Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.


Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



Product Number Builder Example: EL914B



Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**



4" Airtight IC Housing **New Construction**

CAI NO.	
EL99ICA	

SPECIFICATIONS	
Lamp: 50W MAX.	

CAT NO.	SPECIFICATIONS	
EL99A	Lamp: 50W MAX.	

CAT NO.	SPECIFICATIONS	
EL99LDICA	Lamp: LED 12W MAX.	



4" Airtight IC Housing Remodel



4" Housing Remodel




4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

CAT NO.	SPECIFICATIONS	
EL99RICA	Lamp: 50W MAX.	

CAT NO.	SPECIFICATIONS	
FI 99RA	Lamp: 50W MAX.	

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	



4" Airtight IC Housing with GU24 Base Socket **New Construction**



4" Airtight IC Housing with GU24 Base Socket Remodel

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS
FI 99RICA-G24	Lamp: 18W MAX.

4" Accessories



Fire Cover

	K /-
>	





Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H × 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8"

CAT NO.	SPECIFICATIONS
FIRETAPE	³ / ₄ " W × 16' L