

LED Step Light with Frosted Glass Lens

ELCO's Moa Collection consists of damp or wet location standard and mini LED Step Lights with or without a photocell which are offered in 3000K, 120V or 12V AC with an Angled Louver or acrylic lens in a sharp White, Black, Nickel or Bronze powder coated finish.



Features

- Galvanized stamped steel housing.
- Powder coated faceplate.
- Integrated LED board and driver.
- UL Listed for direct contact with insulation.
- Side brackets for mounting to wood.
- Life span of 35,000 hours L70.
- Includes hanger bar tabs (sold separately).

Specifications

Wattage	2W
Voltage	120V
Color Temp.	3000K
Lamp Type	LED
CRI	90+
Damp Location	Listed

Options



Black



White



Bronze

Technical Details

Optics: Acrylic lens diffuses light to illuminate walkway.

Construction: Stamped galvanized steel housing with smooth powder coat finish faceplate.

Installation: Easily installs into provided single gang switch box. Includes installation hardware and brackets for mounting to wood.

Electrical:


- Ambient operating temperature -23°F (-5°C) to 113°F (45°C).
- 120V ELST20: Driver input of 120V 50/60Hz connects directly to line voltage power.

LED Technology:

- 90+ CRI for extremely accurate color rendering.
- Lumen Maintenance of 35,000 hours L70 Life.
- Integrated LED board and driver.

Listings: UL and cULus Listed for Damp Location.

Dimensions



Product Numbers

Item	Lamp type	CCT	Watts	Voltage	Finish
ELST20B	LED	3000K	2W	120V	Black
ELST20BZ	LED	3000K	2W	120V	Bronze
ELST20W	LED	3000K	2W	120V	White