Terazio[™] is an alluring recreation of quartz-like attributes in a durable porcelain tile. High-definition inkjets create natural speckled variations on the surface in neutral earth tones. Terazio provides a smooth, luminous finish for residential and commercial applications.





INDOOR

COMMERCIAL

FLOOR / WALL



Gesso





Palladio

Nero

Sizes	24 ["] x24" 23.62 ["] x23.62"	12 ^{°°} x24 ^{°°} 12.2 ^{°°} x24.02 ^{°°}	3"x24" Floor SBN				
Thickness	10mm	10mm	10mm				
Faces	8	16	N/A				
Finish	Polished	Matte	Matte & Polished				
Edge	Pressed	Rectified	Cut/Rounde	ed			
Grout Joint Recommendation	3/16"	1/8"	1/8"				
Testing	Abrasion Resistance	Breaking Strength C648	Chemical Resistance C650	Water Absorption	DCOF ANSI A137.1	Scratch Hardness MOHS	Shade Variation Rating
Results*		≥250 lbf	Resistant	<u><</u> 0.50%	<0.42 (Polished) >0.60 (Matte)	6	V2

Product and Installation Details | ANSI A108.02 Section 4.3.8.2 · For running bond/brick joing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



Sustainability Attributes

Ked List Free
VOC
Health Draduet Dedecation (UDD) and dedecation

Health Product Declaration (HPD) provide
Droduct Deckaging is 100% recyclebility

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.