

Trenton Keyed Plates, Single Cylinder (6030)

- Standard Door Thickness: 1⁵/8"- 2¹/8" Standard Components:
- Single Cylinder Tailpiece
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2¹/4" Deadbolt Mounting Screws
- Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extended Door Thickness: 1³/₄"- 2³/₄" Extended Components:
- · Long Single Cylinder Tailpiece
- · Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2¹/2" & 3" Deadbolt Mounting Screws
- Extended Full-Lip Strike Plate
- · Deadbolt Strike Plate

Trenton Style (Brass), Keyed Plates, Double Cylinder (6031)

- Standard Door Thickness: 1⁵/8"- 2" Standard Components:
- Double Cylinder Tailpiece
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2¹/2" Deadbolt Mounting Screws
- Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extended Door Thickness: 2"- 2⁵/8" Extended Components:
- · Long Double Cylinder Tailpiece
- Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3" Deadbolt Mounting Screws
- Extended Full-Lip Strike Plate
- · Deadbolt Strike Plate
- * Part # DB4-COLLAR32 Available for 13/8" Thick Doors

Cast Bronze Non-Keyed Plates (passage/privacy)

#5 (7107/7207 & 7707/7807), Rectangular Style (71013/72013 & 7512/7612), #16 Style (6102/6202 & 6702/6802)

- Standard Door Thickness: 1¹/4"- 2" Standard Components:
- Privacy Pin (for privacy sets)
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- Full-Lip Strike Plate

- Extended Door Thickness: 2"- 3" Extended Components:
- Privacy Pin w/ Extensions (for privacy sets)
- Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- Extended Full-Lip Strike Plate

Cast Bronze Keyed Plates, Single Cylinder

#5 (7070/7670), Rectangular Style (7360/7560), #16 Style (6020/6620)

- Standard Door Thickness: 1⁵/8"- 2" Standard Components:
- Single Cylinder Tailpiece
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2¹/4" Deadbolt Mounting Screws
- Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extended Door Thickness: 2"- 2³/8" Extended Components:
- · Long Single Cylinder Tailpiece
- · Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2¹/2" Deadbolt Mounting Screws
- Extended Full-Lip Strike Plate
- · Deadbolt Strike Plate

- Extended Door Thickness: 2³/8"- 3" Extended Components:
- Extra Long Single Cylinder Tailpiece
- Extra Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3" & 3¹/2" Deadbolt Mounting Screws
- Extended Full-Lip Strike Plate
- Deadbolt Strike Plate



Cast Bronze Keyed Plates, Double Cylinder

#5 (7071/7671), Rectangular Style (7361/7561), #16 Style (6021/6621)

- Standard Door Thickness: 1¹/2"- 2" Standard Components:
- Single Cylinder Tailpiece
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2¹/2" Deadbolt Mounting Screws
- Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extended Door Thickness: 2"- 2¹/2" **Extended Components:**
- Long Double Cylinder Tailpiece
- · Long Inside Passage Half Spindle
- 1" Wood Screws
- · Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- · 3" Deadbolt Mounting Screws
- · Extended Full-Lip Strike Plate
- · Deadbolt Strike Plate

- Extended Door Thickness: $2^{1/4}$ "- $2^{3/4}$ " Extended Components:
- Long Double Cylinder Tailpiece
- · Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3 1/2" Deadbolt Mounting Screws
- · Extended Full-Lip Strike Plate
- Deadbolt Strike Plate

Wrought Steel #5 Keyed Plates, Double Cylinder (7011)

- Standard Door Thickness: 1⁵/8"- 1³/4" Standard Components:
- Double Cylinder Tailpiece
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3" Deadbolt Mounting Screws
- Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extended Door Thickness: 1³/4"- 2³/8" Extended Components:
- Long Double Cylinder Tailpiece
- Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3¹/2" Deadbolt Mounting Screws
- Extended Full-Lip Strike Plate
- Deadbolt Strike Plate

Wrought Steel Non-Keyed Plate (passage/privacy) (7105/7205)

- Standard Door Thickness: 1¹/₄"- 1³/₄"
 Standard Components:
- Privacy Pin (for privacy sets)
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- Full-Lip Strike Plate

- Extended Door Thickness: 1³/4"- 2³/8" Extended Components:
- Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- · Extended Full-Lip Strike Plate
- Extended Door Thickness: 1³/4"- 2³/8" Extended Components:
- Privacy Pin w/Extension (for privacy sets)• Privacy Pin w/Extension (for privacy sets)
 - · Long Inside Passage Half Spindle
 - 1" Wood Screws
 - Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
 - · Extended Full-Lip Strike Plate

Wrought Steel #5 Style Keyed Plates, Single Cylinder (7010)

- Standard Door Thickness: 1¹/2"- 1³/4"
 Standard Components:
- Single Cylinder Tailpiece
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2¹/4" Deadbolt Mounting Screws
- Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extended Door Thickness: 1³/4"- 2¹/4" Extended Door Thickness: 2¹/4"- 2³/4" Extended Components:
- Long Single Cylinder Tailpiece
- Long Inside Passage Half Spindle
- 1" Wood Screws
- · Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2¹/2" Deadbolt Mounting Screws
- Extended Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extra Long Single Cylinder Tailpiece
- Extra Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3" Deadbolt Mounting Screws
- · Extended Full-Lip Strike Plate
- Deadbolt Strike Plate