

Thin Rosette: #8, Rectangular, Disk, etc...

• Standard Door Thickness: 1¹/4"- 1⁵/8" Standard Components:

- Small Spindle
- 8-32 x 1" Mounting Screws
- Full Lip Strike Plate

• Extended Door Thickness: 1⁵/8" - 2" Extended Components:

- Medium Spindle
- 8-32 x 1" Mounting Screws
- Full Lip Strike Plate

• Extended Door Thickness: 2"-2¹/4" Extended Components:

- Long Spindle
- 8-32 x $1^{1/2}$ Mounting Screws
- Extended Full Lip Strike Plate

Medium Rosette: #2, Oval, Regular, etc...

- Standard Door Thickness: 1¹/4"- 1⁵/8" Standard Components:
- Medium Spindle
- 8-32 x 1" Mounting Screws
- Full Lip Strike Plate

- Extended Door Thickness: 1⁵/8" 2" Extended Components:
- Medium Spindle
- 8-32 x 1" Mounting Screws
- Full Lip Strike Plate

- Extended Door Thickness: 2"-2¹/4" Extended Components:
- Long Spindle
- 8-32 x 1¹/2" Mounting Screws
- Extended Full Lip Strike Plate

Thick Rosette: Neos, Landcaster, Euro, etc...

- Standard Door Thickness: 1¹/4" 1⁵/8" Standard Components:
- Medium Spindle
- 8-32 x 1" Mounting Screws
- Full Lip Strike Plate

- Extended Door Thickness: 1⁵/8" 2" Extended Components:
- Medium Spindle
- 8-32 x 1" Mounting Screws
- Full Lip Strike Plate

- Extended Door Thickness: 2"-2¹/4" Extended Components:
- Long Spindle
- 8-32 x 1¹/2" Mounting Screws
- Extended Full Lip Strike Plate


Thin Rosette: #8, Rectangular, Disk, etc...

Medium Rosette: #2, Oval, Regular, etc...

Thick Rosette: Neos, Landcaster, Euro, etc...







Note: Rosette Dimensions are approximate and will vary

Emtek Products, Inc. 15250 Stafford St. City of Industry, CA 91744 Tel: 800.356.2741 Fax: 800.577.5771 www.emtek.com



Standard Operating Procedures

Group: MANUFACTURING

Latest Revision Date: Title: CFM DOOR THICKNESS

Issue Date: 02-14-2012

