



2<sup>13</sup>/<sub>16</sub>"

3<sup>7</sup>/<sub>16</sub>"

4<sup>5</sup>/<sub>16</sub>"

Order any Sandcast Bronze knob or lever for the inside trim.

#### **Standard with Mortise Locks**

- 2 1/2" or 2 3/4" backsets
- Standard Mortise Door Prep ANSI A115.1
- · Schlage C Keyway

Sonoma Entryset Part # 3329

Longmont Entryset Part # 3330

# Additional Dimensions: (Part # 3329 & 3330)

- Exterior Projection is 3<sup>1</sup>/8"
- · Interior Projection Depends on Handle Style
- Overall Grip thickness: 1<sup>3</sup>/<sub>4</sub>"
- Clearance between door & grip is 13/4"
- Plates thickness: 1/2"

# Same dimensions for dummy function

### Standard Door Thickness: 134"

Standard Components:

- 1 3/8" Threaded Cylinder
- 2" Long Spindle
- 2" Top Rosette Screw
- 1 1/2" Bottom Rosette Screw
- Thumbpress
- Strikeplate

# **Door Thickness Specifications**

#### Extended Door Thickness: 17/8"-21/4"

**Extended Components:** 

- 1 1/2" Threaded Cylinder
- 2" Long Spindle
- 2 1/2" Top Rosette Screw
- 2" Bottom Rosette Screw
- Thumbpress
- Strikeplate

### Extended Door Thickness: 2 3/8"- 2 5/8"

**Extended Components:** 

- 1 ¾" Threaded Cylinder
- 2 ¼" Long Spindle
- 2 1/2" Top Rosette Screw
- 2" Bottom Rosette Screw
- Extended Thumbpress
- Extended Strikeplate
- · 2 ¾" TD Regires 2" Threaded Cylinder