



Door Thickness Specifications		
<p><b>Standard Door Thickness: 1-3/4"</b></p> <p>Standard Components:</p> <ul style="list-style-type: none"> <li>• 1-3/8" Threaded Cylinder</li> <li>• 2" Long Spindle</li> <li>• 2" Top Rosette Screw</li> <li>• 1-1/2" Bottom Rosette Screw</li> <li>• Thumbpress</li> <li>• Strikeplate</li> </ul>	<p><b>Extended Door Thickness: 1-7/8" - 2-1/4"</b></p> <p>Extended Components:</p> <ul style="list-style-type: none"> <li>• 1-1/2" Threaded Cylinder</li> <li>• 2" Long Spindle</li> <li>• 2-1/2" Top Rosette Screw</li> <li>• 2" Bottom Rosette Screw</li> <li>• Thumbpress</li> <li>• Strikeplate</li> </ul>	<p><b>Extended Door Thickness: 2-3/8" - 2-3/4"</b></p> <p>Extended Components:</p> <ul style="list-style-type: none"> <li>• 1-3/4" Threaded Cylinder</li> <li>• 2-1/4" Long Spindle</li> <li>• 2-1/2" Top Rosette Screw</li> <li>• 2" Bottom Rosette Screw</li> <li>• Extended Thumbpress</li> <li>• Extended Strikeplate</li> </ul>