

Product Specifications for E20901-BK			
Job Name:	Job Type:		
Quantity:	Comments		



## E20901-BK Quantum LED Pendant

Finish Glass/Shade Product Category
Black Mini Pendant

Lamping		Measurements		Shippin
Number of Bulb(s)	1	Width	6.00"	Carton \
Light Type	LED	Height	2.25"	Carton \
Bulb Type	PCB	Length	6.00"	Carton I
Max Bulb Wattage	7	Extension	N/A	Carton I
Max Fixture Wattage	7	Back Plate Width	N/A	Carton (
Rated Life	N/A	Back Plate Height	N/A	Master I
Rated Lumens	±490	HCO	N/A	Master I
Color Temp	3000K	Min Overall Height	4.25"	Master I
Bulb(s) Included	Integrated	Max Overall Height	123.00"	Master I
Light Up/Down	Both	Hanging Weight	1.65 lb(s)	Master I
Beam Spread	N/A	Height Adjustable	Yes	Master (
CRI	N/A	Slope	N/A	<b>UPS</b> Shi
Photo Cell Included	N/A	Chain Length	N/A	
Ballast/Driver/Transformer	No	Wire Length	N/A	
Dimmable	Yes	Canopy Width	N/A	
		Canopy Height	N/A	
		Canopy Length	N/A	

Shipping	
Carton Weight	2.29 lb(s)
Carton Width	7.75
Carton Height	6.50
Carton Length	7.75'
Carton Cubic Feet	N/A
Master Pack	6
Master Pack Weight	16.50 lb(s)
Master Pack Width	8.50'
Master Pack Height	14.50'
Master Pack Length	25.00'
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification		Other		Equivalents
Safety Rating	Dry	UPC Code	845094079781	Incandesce

Safety Rating	Dry <b>U</b>	PC Code	84509407978
Energy Star	No <b>M</b>	laterial	Aluminum+Acry
CA Title 24	No		
CA Title 20	No		
ADA	No		

Incandescent Watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2016 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.