



**PRODUCT DESCRIPTION**


Reeded glass tubes are paired with ribbed aluminum LED housings in a Gold finish. The interior frosted glass diffusers soften the high-powered LED boards concealed within. The low-voltage light sources are driven by a commercially rated range voltage LED drivers with universal dimming, allowing them to be used in both residential and decorative commercial or hospitality applications.

**MEASUREMENTS**

DIMENSION : 11.75" L x 11.75" W x 17" H  
 MAX OAH : 140" OAH  
 CANOPY : 11.75" W x 1.5" H x 11.75" L  
 HANGING WEIGHT : 9.3 lb

**LAMPING**

INPUT VOLTAGE : 120-277V  
 LUMENS : 1,350 Rated (960 Del.)  
 BULB : 3 x 5W LED PCB Integrated , 15W Total  
 BULB INCLUDED : (Integrated)  
 DIMMABLE : Only at 120V  
 CRI : 90 CRI  
 COLOR\_TEMP : 3000K



**FINISHES OPTION**



**GLASS**

Clear Ribbed 144

**MATERIAL**

Aluminum

**RATINGS**

cETLus  
 Dry Location



**ADDITIONAL**

SLOPE: 30  
 RATED LIFE 25000 Hours  
 OPERATING TEMPERATURE:  
 -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



**WESTERN DISTRIBUTION CENTER (HEADQUARTER)**  
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746  
**EASTERN DISTRIBUTION CENTER**  
 4200 SHIRLEY DR. | ATLANTA, GA 30336  
 P. 626.956.4200 | F. 626.956.4225 | et2online.com