



*Finish* Satin Nickel

## Lamping Number of Bulb(s) Light Type Bulb Type Max Bulb Wattage Max Fixture Wattage Rated Life

±2,000 Hours
±750
±2,900 K
Yes
N/A
N/A
N/A
N/A
No
Low-Voltage

Glass/Shade Clear/White

	Measurements	
1	Width	5.00"
Xenon	Height	7.00"
12V GY6.35 T4	Length	N/A
50	Extension	N/A
50	Back Plate Width	N/A
±2,000 Hours	Back Plate Height	N/A
±750	НСО	N/A
±2,900 K	Min Overall Height	N/A
Yes	Max Overall Height	N/A
N/A	Hanging Weight	0.35 lb(s)
N/A	Height Adjustable	N/A
N/A	Slope	N/A
N/A	Chain Length	N/A
No	Wire Length	120.00"
Low-Voltage	Canopy Width	N/A
	Canopy Height	N/A
	Canopy Length	N/A

## Product Specifications for EP96038-10SN

Job Name:	Job Type:
Quantity:	Comments

## EP96038-10SN

Frost 1-Light RapidJack Pendant

## Product Category RapidJack Pendant

	Shipping	
5.00"	Carton Weight	0.60 lb(s)
7.00"	Carton Width	6.00"
N/A	Carton Height	6.00"
N/A	Carton Length	9.25"
N/A	Carton Cubic Feet	N/A
N/A	Master Pack	1
N/A	Master Pack Weight	N/A
N/A	Master Pack Width	N/A
N/A	Master Pack Height	N/A
lb(s)	Master Pack Length	N/A
N/A	Master Cubic Feet	N/A
N/A	UPS Shippable	Yes
N/A		
0.00"		
N/A		

Certification	Other		Equivalents	
Safety Rating	Dry UPC Co	<b>de</b> 845094051282	Incandescent Watts	N/A
Energy Star	No Materia	N/A	Fluorescent Watts	N/A
CA Title 24	No			
CA Title 20	No			
ADA	No			

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.

253 North Vineland Avenue | City of Industry, California 91746 | 800.486.2946p 800.486.7337f | www.et2online.com