

Product Specifications for E22467-75PC								
	Job Name:	Job Type:						
	Quantity:	Comments						

-		***************************************	***************************************	***************************************	
nun	ni in	el la	nun.	NUN	
-	-		-	-	
-	-	-	-	6000	

E22467-75PC

Tyme 5-Light LED Pendant

Finish Polished Chrome		Glass/Shade Clear Acrylic		Product Category	
Lamping	_	Measurements		Shipping	40.00 !! ()
Number of Bulb(s)	5	Width	37.25"		18.00 lb(s)
Light Type	LED	Height	6.25"	Carton Width	9.80"
Bulb Type	LED	Length	4.75"	Carton Height	11.00"
Max Bulb Wattage	3	Extension	N/A	Carton Length	39.40"
Max Fixture Wattage	15	Back Plate Width	N/A	Carton Cubic Feet	N/A
Rated Life	±40,000 Hours	Back Plate Height	N/A	Master Pack	1
Rated Lumens	±1,200		N/A	Master Pack Weight	N/A
Color Temp		Min Overall Height	N/A	Master Pack Width	N/A
Bulb(s) Included	Yes	Max Overall Height	129.75"	Master Pack Height	N/A
Light Up/Down	N/A	Hanging Weight	16.50 lb(s)	Master Pack Length	N/A
Beam Spread	N/A	Height Adjustable	Yes	Master Cubic Feet	N/A
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	No	Wire Length	N/A		
Dimmable	Low-Voltage Electronic Dimmer	Canopy Width			
		Canopy Height			
		Canopy Length	N/A		
Certification		Other		Equivalents	
				•	
Safety Rating	DRY	UPC Code	845094061151	Incandescent Watts	N/A
Energy Star	No	Material	N/A	Fluorescent Watts	N/A
CA Title 24	No				
CA Title 20	No				
ADA	No				

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.