


Product Specifications for	or E41302-WT
I.I. M	I.1. T

 1 Todast opcomoditorio for E 1 Tota 111		
Job Name:	Job Type:	
Quantity:	Comments	



E41302-WT **Alumilux AL 18-Light LED Wall Mount**



*height from center of outlet to the top of the fixture

Fil	ni	is	ŀ
\ \/ /	hit	-	

Lamping

Number of Bulb(s)

Light Type LED **Bulb Type** LED Max Bulb Wattage .30 **Max Fixture Wattage** 5.4 **Rated Life** ±5,000 Hours **Rated Lumens** ±445 **Color Temp** ±3,000 K Bulb(s) Included Integrated Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No

Glass/Shade

18

No

Measureme	nts
Width	

Width	7.25"
Height	4.50"
Length	N/A
Extension	5.25"
Back Plate Width	N/A
Back Plate Height	N/A
НСО	2.25"
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	2.20 lb(s)
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Wall Sconce

	n	

Shipping	
Carton Weight	3.00 lb(s
Carton Width	6.30
Carton Height	10.24
Carton Length	7.87
Carton Cubic Feet	N/A
Master Pack	4
Master Pack Weight	15.40 lb(s
Master Pack Width	11.02
Master Pack Height	13.39
Master Pack Length	16.54
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Dimmable

Safety Rating	Wet
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Other

Other	
UPC Code	845094060451
Material	Aluminum

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2015 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.