



Exit Device Application Guide

Single Door




Rim Type (8000 or F8000 Series)

Double Doors with Mullion




2 Rim Type with Mullion (8000 or F8000 Series)

Double Doors without Mullion




1 Vertical Rod and 1 Rim Type (8100, F8100 or F8100 LBR and 8000 or F8000 Series) Overlapping Strike # 9285 Recommended

Double Doors without Mullion



2 Vertical Rod Type (8100, F8100 or F8100 LBR Series)

Double Doors without Mullion



2 Vertical Rod Less Bottom Rod (F8100 LBR Series)

Exit Device Product Selector

Application	Fire Rated Model	Non-Fire Rated Model	Maximum Door Opening
Single Doors	F8000-36	8000-36	4′0″ x 8′0″
Rim Type	F8000-48	8000-48	
Double Doors without Mullion	F8100-3684	8100-3684	8′0″ x 7′2″
Two surface mounted standard Vertical Rod Type. For	X	X	
Vertical Rod Less Bottom Rod, specify LBR	F8100-3684	8100-3684	
a) Swinging in same direction	F8000-4896	8000-4896	8′0″ x 8′0″
b) Swinging in opposite direction (Double Egress)	X	X	
	F8100-4896	8100-4896	
Double Doors with Mullion	F8000-36	8000-36	8′0″ x 8′0″
Two Rim Type	F8000-48	8000-48	