



*Dimension when used with BPD4A blades. Ceiling to blade measurement will vary depending on blade.

BELLERIA®

FP4320**1 Wet-Location Ceiling Fan

Available Finishes	
AZ	Aged bronze
LT	Latte
MW	Matte white
TB	Textured black
TS	Tortoise shell

	A	B*
Fan w/6" downrod	16.30"	15.00"
Fan w/12" downrod	22.30"	21.00"
Fan w/18" downrod	28.30"	27.00"
Fan w/24" downrod	34.30"	33.00"
Fan w/36" downrod	46.30"	45.00"
Fan w/48" downrod	58.30"	57.00"
Fan w/60" downrod	70.30"	69.00"
Fan w/72" downrod	82.30"	81.00"

INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 50 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

188 x 25 motor is designed for optimal performance with this fan. 220 VAC, 50 Hz export version available.

BLADES:

All-weather composite, palm, bamboo, and wood blade sets are available—sold separately. See our catalog or visit www.fanimation.com for all available blade options.

CONTROL OPTIONS (Dry Applications Only):

Optional CW1, CW1SW, CW2, CW5 and CWRL4 wall controls available—sold separately. Optional CRL4WH and CRL8TS remote controls with canopy-style receiver unit available—sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

Optional lighting fitters and light kits are available. Lighting fitter FW423 is water-sealed and UL wet location approved. See our catalog or visit www.fanimation.com for available lighting options.

DOWNROD OPTIONS:

Fan comes with 1" dia. x 6" long wet-location downrod (DR1-6). Optional wet-location downrods are available in 12", 18", 24", 36", 48", 60" and 72" lengths. Fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 6" downrod. Optional sloped ceiling ball kits (SCB1-52) are available for slope angles greater than 30° and up to 52°. Optional close-to-ceiling kit is available as well-sold separately. Call technical support for more information.

LOCATION USE:

Rated for dry, damp and wet locations.

Airflow / Energy Efficiency Info (120V)					
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
High	163	5580	67	0.70	83
Med	104	3475	96	0.46	36
Low	70	2197	124	0.32	18

Available All-Weather Composite Blades		
Palm leaf	BPP1	Natural - 22" wide oval
Palm leaf-brown	BPP1BR	Painted - 22" wide oval
Palm leaf	BPP4	Natural - 22" narrow oval
Palm leaf-brown	BPP4BR	Painted - 22" narrow oval
Palm leaf-green	BPP4GR	Painted - 22" narrow oval
Woven bamboo	BPD1A	Antique - 22" Wide oval
Woven bamboo	BPD4A	Antique - 22" narrow oval
Woven bamboo	BPD4MW	Matte white - 22" narrow oval
Woven bamboo	BPD5A	Antique - 18" narrow oval
Traditional wood	BPW10CY	Cherry - 20" narrow
Curved-edge wood	BPW20CY	Cherry - 20" narrow
Curved-edge wood	BPW20MH	Mahogany - 20" narrow
Curved-edge wood	BPW20TK	Teak - 20" narrow