# The Torto<sup>™</sup>

**FP7900** 




## SPECIFICATION SHEET



celebrating 25 years

Product Specifications subject to change

### The Torto<sup>™</sup> Fan Assembly – FP7900\*\*



Available Finishes			
MG	Metro Gray		
ОВ	Oil-Rubbed Bronze		

Distance from Ceiling to Edge of Blade	Α	
Fan w/6" downrod	15″	
Fan w/12" downrod	21″	
Fan w/18" downrod	27″	
Fan w/24" downrod	33″	
Fan w/36" downrod	45″	
Fan w/48" downrod	57″	
Fan w/60" downrod	69″	
Fan w/72" downrod	81″	

Airflow / Energy Efficiency Info (120V)								
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts			
High	106	4400	76	0.49	58			
Med	88	2800	79	0.44	36			
Low	66	1700	93	0.34	18			

#### **INSTALLATION REQUIREMENTS:**

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 50 lbs.

#### **ELECTRICAL REQUIREMENTS:**

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

#### **MOTOR SPECS:**

172 x 20 motor is designed for optimal performance with this fan.

#### **BLADE SET:**

Three composite blades are included.

#### **CONTROL OPTIONS:**

C20 hand-held reversing remote control with canopy-style receiver unit (RECAN68) is included. Push button remote control has 3 fan speeds, infinite light levels, reverse and off button. Optional C21 wall control is available—sold separately. Instructions are provided with each control.

#### **LIGHTING OPTIONS:**

2-bulb built-in downlight fixture with two 60-watt candelabra bulbs is included. Maximum downlight wattage is not to exceed 120 watts.

#### **DOWNROD OPTIONS:**

Fan comes with a 1" dia. x 6" long downrod (DR1-6). Optional downrods available in 12", 18", 24", 36", 48", 60" and 72" lengths. Fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 6" downrod. Call technical support for more information.

#### **LOCATION USE:**

Fan is rated for dry and damp locations.



10983 Bennett Parkway
Zionsville, IN 46077
Toll Free (888) 567-2055
FAX (866) 482-5215
Outside U.S. call (317) 733-4113
Visit Our Website www.fanimation.com

