
VENTANA™ FP8032SB Ceiling Fan





INSTALLATION REQUIREMENTS:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding a load of at least 50 lbs.

ELECTRICAL REQUIREMENTS:

Ceiling fan requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

172 x 17 motor is designed for optimal performance with this fan.

BLADE SETS:

A set of five 20.7" reversible mahogany/walnut wood blades is included.

Amps	Watts
0.61	74
0.50	37
	0.61

1496

Airflow / Energy Efficiency Info (120V)

Fan w/4.5" downrod

Fan w/12" downrod

Fan w/18" downrod

Fan w/24" downrod

Fan w/36" downrod

Fan w/48" downrod

Fan w/60" downrod

Fan w/72" downrod

SB

Low

Available Finish

Sedona Beige with Amber Tea glass

136

Α

18.38"

25.88"

31.88"

37.88

49.88

61.88

73.88"

85.88"

0.31

11

В

10.59"

18.09"

24.09"

30.09"

42.09"

54.09"

66.09"

78.09"

CONTROL OPTIONS:

TR24WH hand-held remote control with wall mount is included. Push button remote control has 3 fan speeds, infinite light levels and off button. Optional CWRL4 and C25 wall controls, CRL4WH and CRL8TS hand-held remote controls are available—sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

Two-bulb (50-watt halogen minican bulbs -included) downlight fixture is included with this fan assembly. Maximum downlight wattage not to exceed 100 watts.

DOWNROD OPTIONS:

The Ventana[™] fan comes with a 1″ Dia. x 4.5″ downrod. Optional downrods are available in 12″, 18″, 24″, 36″, 48″, 60″, and 72″. For installations requiring a longer downrod, a downrod coupler is available. The Ventana[™] fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 4.5″ downrod. Optional sloped ceiling ball kits (SCB1-52) are available for up to 52°. Optional close-to-ceiling kit is available as well—sold separately. Call your local dealer for more information.

LOCATION USE:

Fan is rated for dry locations only.