
# **HUBBARDTON FORGE® SERIES**

# HF7600DS Presidio Tryne<sup>™</sup> Fan





## **INSTALLATION REQUIREMENTS:**

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 50 lbs.

### **ELECTRICAL REQUIREMENTS:**

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

#### **MOTOR SPECS:**

188 x 25 motor is designed for optimal performance with this fan.

#### BLADES:

A set of five coffee slate wood blades is included.

#### **CONTROL OPTIONS:**

TR22WH hand-held remote control with wall mount is included. Push button remote control has 3 fan speeds, reverse, off button and infinitely-varying uplight and downlight controls. Instructions are provided with each control.

#### LIGHTING OPTIONS:

Decorative uplight kit with three 25-watt candelabra bulbs and Presidio Tryne<sup>™</sup> downlight kit with three 40-watt candelabra bulbs are included. Maximum uplight wattage is not to exceed 75 watts and maximum downlight wattage is not to exceed 120 watts.

#### **DOWNROD OPTIONS:**

Fan comes with a 1" dia. x 6" long downrod (DR1-6). Optional downrods available in 12", 18", 24", 36", 48", 60" and 72" lengths. Fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 6" downrod. Optional sloped ceiling ball kits (SCB1-52) are available for slope angles greater than 30° and up to 52°. Optional close-to-ceiling kit is available as well—sold separately. Call technical support for more information.

#### LOCATION USE:

Fan is dry location rated only. Damp location rated when used with optional all-weather composite blade set (BPW21CF).

All Hubbardton Forge designs, the mark HUBBARDTON FORGE and the design of the tongs are trademarks or registered trademarks of Hubbardton Forge Corporation.



	Α	В
Fan w/6" downrod	21.45″	15.35″
Fan w/12" downrod	27.45″	21.35″
Fan w/18" downrod	33.45″	27.35″
Fan w/24" downrod	39.45″	33.35″
Fan w/36" downrod	51.45″	45.35″
Fan w/48" downrod	63.45″	57.35″
Fan w/60" downrod	75.45″	69.35″
Fan w/72" downrod	87.45″	81.35″

Available Finish					
Model	Model Fan Finish		Glass		
HF7600DS	Dark Smoke	Slate	Opal		

Airflow / Energy Efficiency Info (120V)						
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts	
High	163	5784	81	0.61	72	
Med	102	3470	109	0.39	32	
Low	64	2052	136	0.26	15	