

Freestanding Range

FPGH3077RE



Signature Features



PowerPlus® 2-in-1 **Burner & Griddle**

Ultimate cooking flexibility for endless meal options. Use the simmer burner for delicate foods like sauces or the griddle burner for pancakes or



PowerPlus® Temperature Probe

Ensures great results the first time. Set and monitor dish temperature with the PowerPlus® Temperature Probe.



PowerPlus® Convection

Powerful performance delivers consistent results. Evenly cooked dishes, every time, with PowerPlus® Convection Bake and Roast.



PowerPlus® Preheat

With PowerPlus® Preheat, your oven is ready in a few minutes for a powerful start to every delicious meal.

30" Gas

Product Dimensions

Height (Max.) 36-5/8" Width 30" Depth (Including Handle) 28-5/16"

More Easy-To-Use Features

Smudge-Proof™

Resists fingerprints and cleans easily.

Professional-Grade Design, Without the Remodel

Upgrade your kitchen and get the look of a built-in range, without the remodel. The range slides into 30" cutouts.1

Built with American Pride

Designed, engineered and assembled in the U.S.A.

PowerPlus® Burner

Quickly boil, saute, and sear foods at high heat with the PowerPlus 18,000 BTU burner.

PrecisionPro Controls™

Prepare a range of dishes with precision, whether you're simmering, sautéing, searing or boiling.

Convection Conversion

Automatically converts the convection oven to the ideal cooking time for evenly cooked dishes.

A.D.A. Compliant

When properly installed, this model is A.D.A.-qualified based on the United States Access Board's A.D.A./A.B.A. Accessibility Guidelines and the Department of Justice's 2010 A.D.A. Standards for Accessible Design.

Sabbath Mode (Star-K* Certified)

Available in:




Burners	BTU
Right Front	18,000
Right Rear	5,000
Left Front	9,500
Left Rear	12,000
Center Griddle	8,500
Center Simmer	500-3,500

¹Fits the cutout of a 30" freestanding range.

FPGH3077RF 30" Gas

Features	
Oven Control/Timing System	PrecisionPro Controls™
Surface Type	Deep Sump Stainless Stee
Sealed Gas Burners	Yes
Grates	Continuous Cast Iron w/Black Matte Finish
Window	Extra-Large with Black-Tint Finish
Exterior Door Finish	Smudge-Proof™ Stainless Steel
Handle Design	Stainless Steel
Exterior Finish (Side Panels)	Black
Convection System	PowerPlus® Single-Fan Convection
Oven Cleaning System	Self Clean
Drawer Functionality	Storage
Oven Controls	
Bake/Broil	Yes/Yes
Effortless™ Convection Conversion	Yes
Convection Bake/Broil/Roast	Yes/No/Yes
PowerPlus* Convection	Yes
PowerPlus* Preheat	Yes
My Favorite	
Slow Cook	
PowerPlus® Temperature Probe	Yes
Keep Warm	Yes
Add-a-Minute	100
Delay Start	
Self Clean	2, 3, 4 Hours
Rapid Clean Option	2 Hours
Delay Clean	2110410
Kitchen Timer/Timed Cook Option	Yes (2)/No
Auto Oven Shut-Off	Yes
Oven Lock-Out	Yes
Lower Drawer Control	1.00
Cooktop Features	
<u> </u>	
Right Front Burner (BTU)	18,000
Right Rear Burner (BTU)	5,000
Left Front Burner (BTU)	9,500
Left Rear Burner (BTU)	12,000
Center Griddle Burner (BTU)	8,500
Center Simmer Burner (BTU)	500 - 3,500
Oven Features	
Capacity (Cu.Ft.)	5.1
Oven Light	2
Hidden Bake Element	
Rack Configuration	1 PowerGlide™, 1 Handle,
	1 Offset
Baking System	Even Baking Technology
Broiling System	
Bake Burner/Broil Burner (BTU)	18,000/11,500
Drawer Racks	
Optional Accessories	
Griddle/Grill (2-sided)	Included
Certifications	
	Vee
A.D.A. Compliant ¹	Yes
	Yes
Sabbath Mode (Star-K® Cert.)	
Sabbath Mode (Star-K* Cert.) Specifications	
	18-5/8" x 24-1/8" x 19-1/2"
Specifications	18-5/8" x 24-1/8" x 19-1/2" Left Bottom Rear
Specifications Oven Interior (H x W x D)	
Specifications Oven Interior (H x W x D) Power Supply Connection Location	Left Bottom Rear
Specifications Oven Interior (H x W x D) Power Supply Connection Location Gas Supply Connection Location	Right Bottom Rear
Specifications Oven Interior (H x W x D) Power Supply Connection Location Gas Supply Connection Location LP Gas Conversion Kit	Left Bottom Rear Right Bottom Rear Included



NOTE: For planning purposes only. Always consult local and national electric and gas codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com.



Product Dimensions	
A - Height (Max.)	36-5/8"
B-Width	30"
C-Depth (Including Handle)	28-5/16"
Depth with Door Open 90°	47-9/16"

Cabinet Cutout Dimensions	
Height (Standard)	36"
Width (Min.)	30-1/8"
Depth (Min.)	25"

¹When properly installed, this model is A.D.A.-qualified based on the United States Access Board's A.D.A./A.B.A. Accessibility Guidelines and the Department of Justice's 2010 A.D.A. Standards for Accessible Design.

Accessories information available on the web at **frigidaire.com**

FRIGIDAIRE.

Shipping Weight (Approx.)

230 lbs.