# **FRIGID**AIRE

# Home Comfort



## **Signature Features**

### Effortless™ Temperature Control

Our air conditioners maintain the preset room temperature, so you will remain comfortable at all times.

# Supplemental Heating Option

Our versatile unit offers a supplemental heating capability, providing you with an additional heat source when needed.

## **Ready-Select® Controls**

Easily select options with the touch of a button.

## **Remote Control**

Allows you to precisely control the temperature and fan speed from across the room.



## Compact Slide-Out Chassis Air Conditioner/Heat Pump

#### **Product Dimensions**

Height	15-3/8″	
Width	22-5/8″	
Depth	23-5/16"	

#### More Easy-To-Use Features

#### Effortless™ Clean Filter

Our antibacterial filter reduces bacteria, room odors and other airborne particles for a cool, comfortable environment.

#### Multi-Speed Fan

Features three different fan speeds, for more cooling flexibility.

#### Sleep Mode

Quiet operation keeps you cool without keeping you awake. Plus, Sleep Mode gradually increases room temperature after being activated.

#### **Quickly Cools**

Quickly cool a room on hot days.

#### **Comfort Control Design**

Easily control the direction of your cool air, wherever your unit is.

#### Effortless<sup>™</sup> Restart

Automatically resumes operating at its previous settings when power is restored to your unit.

#### **Clean Filter Alert**

Notifies you when your filter needs to be cleaned.

#### **Power Cord**

Comes with an extra long three-prong cord — makes extension cords unnecessary.

#### SpaceWise® Adjustable Design Optional Side Panels

Extend so you can adjust your unit to fit your window.

#### 24-Hour On/Off Timer

Keep things cool on your schedule.


Performance	BTUs
Cool	8,000
Heat	3,500
Heat Pump	7,000

# FRIGIDAIRE

# Home Comfort

FRA08PZU1 Compact Slide-Out Chassis Air Conditioner / Heat Pump

Performance		
BTU (Cool)	8,000	
BTU (Heat)	3,500	
BTU (Heat Pump)	7,000	
Dehumidification (Pints/Hour)	1.5	
Cool Area (Sq. Ft.)	350	
Energy Efficiency Ratio	9.8	
Electrical		
Volts	115	
Amps (Cool)	7.4	
Amps (Heat)	11.6	
Amps (Heat Pump)	7.4	
Watts (Cool)	815	
Watts (Heat)	1,290	
Watts (Heat Pump)	780	
Length of Power Cord (Min./Max.)	6'/6.5'	
Plug Type (NEMA)	LCDI (5-15P)	
Features		
Electronic Controls	Ready-Select* Controls	
Fan Speeds (Cool/Fan/Heat)	3/3/1	
Low Voltage Start-Up	Yes	
Auto Cool Function	Yes	
Energy Save	Yes	
Sleep Mode	Yes	
Filter Check	Yes	
24-Hour On/Off Timer	Yes	
Clean Air Ionizer		
Remote Control	Full-Function with Heat	
Air CFM (High/Med/Low)	278/252/216	
Air Direction Control	8-Way	
Fresh Air/Exhaust Vent/Closed	No/No/Yes	
Filter Type	Antibacterial Mesh	
Filter Access	Tilt-Out	
Slide-Out Chassis	Yes	
Window Mounting Kit (Included)	Pleated Quick Mount	
Warranty <sup>1</sup>	Yes	
Certifications		
Performance	AHAM	
Specifications		
Refrigerant	R410a	



Warranty 5 year sealed system/1 year full parts and labor.



NOTE: For planning purposes only. Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com.



Product Dimensions		Window D
A - Height	15-3/8″	D-Height (M
B-Width	22-5/8″	E-Width (Mi
C-Depth	23-5/16″	Wall Cutou

Window Dimensions	
D-Height (Min.)	16-1/2″
E-Width (Min./Max.)	26-7/8"/36"
Wall Cutout Dimensions	
Height	16-1/8″
Width	23-3/16″
Max. Wall Thickness	6-1/8″

Accessories information available on the web at **frigidaire.com** 

Specifications

#### FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca FRA08PZUI 11/11 © 2011 Electrolux Home Products, Inc.